

MATERIAL SAFETY DATA SHEET
May be used to comply with
OSHA's Hazard Communication
Standard, 29CFR 1910.2100.

U.S. DEPARTMENT OF LABOR
Occupational Safety and
Health Administration
(Non-Mandatory Form)

006-NOZZLE GEL

KCI, INC
3710 N. DAVIDSON STREET
CHARLOTTE, N.C. 28205

CHEMTREC (24-HOUR) 800-424-9300
INFORMATION 704-372-8435
DATE PREPARED: JANUARY 14, 2004

SECTION II-HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous components	OSHA PEL	ACGIH TLV	%(optional)
None	N/A	N/A	

The ingredients in this product are not listed in 29 CFR 1910 Subpart 2 nor do they appear in "Threshold Limit Values for Chemical Substances in the work environment adopted by ACGIH for 1985-86." They are also not reportable under Section 313 of Title III of SARA.

SECTION III-PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: NDA	Specific Gravity(H ₂ O=1) .815-.880
Vapor Pressure: NDA	Melting Point: 100.4-140 F
Vapor Density: NDA	Evaporation Rate: NDA (BUTYL=1)

Solubility in Water: NIL
Appearance and Odor: Opaque, no odor
Volatile(by weight %): 0 at 25C.

SECTION IV-FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used)	Flammable Limits	LEL	UEL
Greater than 390F(astm D-92)	NDA	NDA	NDA

Extinguishign Media: Carbon dioxide, dry chemical or foam.
Special Firefighting Procedures: Pressure-demand, self-contained protection should be provided.
Water spray is an unsuitable extinguishing agent.

Unusual Fire and Explosion Hazards: NONE

SECTION VII-PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to Be Taken in Case Material Is Released or Spilled:

Shut off leak and dike up large spills. After cooling and solidification, scrape and/or shovel up material. Finally, clean area with an oil absorbent material.

Waste Disposal Method:

Dispose of in accordance with local, state, and federal regulations.

Precautions to Be Taken in Handling and Storing:

Store away from flame, heat (250F) maximum. Also keep away from strong oxidizing agents.

Other Precautions:

None

SECTION VIII-CONTROL MEASURES

Respiratory Protection (Specify type)
None required.

Ventilation: Local Exhaust-N/A

Special-N/A

Mechanical- N/A

Other-N/A

Protective Gloves- Impervious when molten. Eye Protection-Wear a face shield if product is molten

Other Protective Clothing: When molten ,wear coveralls.

Work/Hygienic Practices: NDA

006-NOZZLE GEL

PAGE 4 OF 4

NEW JERSEY RIGHT TO KNOW INFORMATION (HAZARDOUS & NON-HAZARDOUS)

USP PETROLATUM	CAS# 8009-03-8	99.5%
ANTHRAQUINONE BLUE DYE	CAS#14233-37-5	.5%

PERCENT VOLATILES: NIL
VOC'S: NONE

HAZARD RATINGS
FIRE-1
REACTIVITY-0
TOXICITY-0
SPECIAL-NONE