

MATERIAL SAFETY DATA SHEET



11/03

MSDS Name: BRIGHT WHITE ACRYLIC PRIMER
MSDS Number: PF4011-49
Version Number: 0009
MSDS Date: 05/07/02
Page Number: 1 of 5

Portland, Oregon
800-554-4666
Orangeburg, S.C.
888-891-7765

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: BRIGHT WHITE ACRYLIC PRIMER
CAS Number: MIXTURE
Hazard Rating: Health: 1 Fire: 1 Reactivity: 0 PPI: E
EPA Registration: NA

Company Identification: Associated Chemists, Inc.
4401 S.E. Johnson Creek Blvd.
Portland OR 97222

Contact: CUSTOMER SERVICE
Telephone/Fax: (503) 659-1708 (503) 653-0409
Emergency Phone (24 Hour): INFOTRAC
(800) 535-5053
Preparer: ROBERTA M. DECHERT
MARKETING MGR.

Product Class: WATERBASE PAINT
Trade Name: MILLWORK PRIMER
Product Code: PF4011-49

SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredients CAS Number % TSCA Health Fire React PP
(No hazardous ingredients known at this time.)

SECTION III - HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

Ingestion and/or inhalation.

CARCINOGENICITY:

This product does not contain any substance(s) listed as a carcinogen by NTP, IARC, or OSHA.

ACUTE (SHORT TERM) FOR PRODUCT:

EYES: Causes irritation.

SKIN: May cause skin irritation upon prolonged or repeated contact.

BREATHING: Causes slight irritation to nose and throat.

SWALLOWING: Ingestion may cause nausea, vomiting, diarrhea.

CHRONIC (LONG TERM) FOR PRODUCT OR COMPONENTS:

Prolonged or repeated breathing of sprays, mists, or dusts in excess of the suggested TLV may cause nasal and respiratory irritations.

PERMISSIBLE EXPOSURE LEVEL FOR PRODUCT:

No Threshold Limit Value (TLV) has been established for the product.

Current Adopted Values listed by ACGIH suggests a TLV of 10 mg/m3

128

MATERIAL SAFETY DATA SHEET

MSDS Name: BRIGHT WHITE ACRYLIC PRIMER
MSDS Number: PF4011-49
Version Number: 0009
MSDS Date: 05/07/02
Page Number: 2 of 5

as Inhalable Particulates Not Otherwise Classified for sprays, mists or dust particulates generated during application or handling exposures.

SECTION IV - FIRST AID MEASURES

- IF IN EYES: Immediately flush eyes with plenty of water for at least 15 minutes. If irritation continues, see a physician.
- IF ON SKIN: Flush skin with water.
- IF SWALLOWED: Induce vomiting. Call a physician immediately. Give large amounts of water or milk. Never give anything by mouth to an unconscious or convulsing person.
- IF BREATHED: Remove person to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Call a physician.

SECTION V - FIRE-FIGHTING MEASURES

Flammability Class	IIIB
Flash Range:	>200F
Explosive Range:	Not Applicable

EXTINGUISHING MEDIA:

Extinguishing media: Product is non-combustible.

SPECIAL FIREFIGHTING PROCEDURES:

Use self-contained breathing apparatus with full facepiece.

UNUSUAL FIRE & EXPLOSION HAZARDS:

None.

SECTION VI - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

SMALL SPILLS: Contain spill immediately. Use inert material to absorb spilled material. Place absorbed spill into secure container for removal.

LARGE SPILLS: Use caution; spilled material may be extremely slippery. Contain spill immediately and prevent from entering the sewer system. Use an inert material to absorb spilled product.

NOTE: Rinsing this material down a sanitary sewer system can cause negative impact on monitoring systems. Contact local sewer authorities before attempting any discharges.

128

MATERIAL SAFETY DATA SHEET

MSDS Name: BRIGHT WHITE ACRYLIC PRIMER
MSDS Number: PF4011-49
Version Number 0009
MSDS Date: 05/07/02
Page Number: 3 of 5

SECTION VII - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:
PROTECT FROM FREEZING. Store above 40 deg. F. Frozen product may be irreversibly damaged.
Keep container closed when not using. Agitate before using.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits					
	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL

RESPIRATORY PROTECTION:
Use an approved MSHA or NIOSH respirator for nuisance mists, dusts, or sprays.

VENTILATION:
Use adequate ventilation to keep airborne concentrations below the exposure standard listed in Section II and/or Section V.

PROTECTIVE GLOVES:
None normally required. Use is advisable.

EYE PROTECTION:
Wear approved splashproof chemical goggles. In a controlled environment where eye contact is minimal, Safety glasses with side shields may be sufficient protection.

OTHER PROTECTIVE EQUIPMENT:
Avoid contact with clothing, dried product may be irremovable.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Form:	LIQUID
Appearance/Color:	WHITE
Odor:	MILD
Solubility (in water):	DISPERSIBLE IN WATER
pH Value:	9.25-9.75
Boiling Range:	(WATER) 212.F (100.C)
Vapor Pressure (mmHg):	(WATER) 17.@ 68.F (20.C)
Melting Point:	Not Available
Evaporation Rate:	Unavailable
Vapor Density:	Non Volatile
Partition Coefficient	Not Available
% Volatile Volume	INCLUDING WATER 51.07%
Specific Gravity:	1.62483
VOC	SEE SECTION XVI
Molecular Weight:	MIXTURE

SECTION X - STABILITY AND REACTIVITY

128

MATERIAL SAFETY DATA SHEET

MSDS Name: BRIGHT WHITE ACRYLIC PRIMER
MSDS Number: PF4011-49
Version Number 0009
MSDS Date: 05/07/02
Page Number: 4 of 5

Stability: This product is stable
Hazardous Polymerization: Hazardous polymerization will not occur

INCOMPATIBILITY:

None

CONDITIONS TO AVOID:

Acids, strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or burning may produce carbon monoxide and/or carbon dioxide.

SECTION XI - TOXICOLOGICAL INFORMATION

Lethal Dose Information (ppm)

ADDITIONAL TOXICOLOGICAL DATA FOR PRODUCT AND/OR INGREDIENTS:
None known for product.

SECTION XII - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION FOR PRODUCT AND/OR INGREDIENTS:
Aquatic toxicity not available.

SECTION XIII - DISPOSAL CONSIDERATIONS

EPA Hazardous Waste Number NONE

WASTE DISPOSAL METHOD:

Product must be disposed of properly under Federal/State regulations for industrial waste. Disposal to a landfill may be permitted pending compliance with 40 CFR 264.314 & 265.314. This product when spilled or disposed of is a non-hazardous waste as defined in RCRA regulations (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

UN Number NONE
UN Pack Group NA
UN Class NA
ICAO/IATA Class NONE
Shipping Name BRIGHT WHITE ACRYLIC PRIMER
DOT Hazard Class NOT HAZARDOUS
Technical Name

CANADIAN TDG/WHMIS INFORMATION:

PIN NUMBER: None

TDG: NA

128

MATERIAL SAFETY DATA SHEET

MSDS Name: BRIGHT WHITE ACRYLIC PRIMER
MSDS Number: PF4011-49
Version Number 0009
MSDS Date: 05/07/02
Page Number: 5 of 5

TDG ACT CLASS: NA

WHMIS: D2B

OTHER NAMES: None

SECTION XV - REGULATORY INFORMATION

EEC Classification Irritant

This product is not a listed hazardous substance.

SECTION XVI - OTHER INFORMATION

ADDITIONAL PRECAUTIONS AND NOTES:

Do not dilute or mix with other materials unless advised by supplier.

VOC INFORMATION

A Certified Product Data Sheet (CPDS) as outlined under Title 40 Part 63, Subpart JJ, Section 63.801 Definitions, detailing VOC content, will be available upon request from Associated Chemists Inc. Environmental Department.