

M A T E R I A L S A F E T Y D A T A S H E E T

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

THIS MATERIAL SAFETY DATA SHEET IS AVAILABLE IN SPANISH UPON REQUEST.

LOS DATOS DE SEGURIDAD DEL PRODUCTO PUEDEN OBTENERSE EN ESPANOL SI LO REQUIERE.

PRODUCT NAME : DERUSTO RPE SPRAY PAINT - ALL COLORS AND CLEAR
 UPC NUMBER : 51719, 51729, 51739, 51749, 51769, 51789, 51799,
 51979, 51989, 51999, 52019, 52029, 52049, 52059,
 52069, 52089, 52119, 52129, 52236, 52237, 52239,
 52246, 52247, 52249, 52279, 52289, 52299, 52309,
 52319, 52329, 52559, 52939, 54622
 PRODUCT USE/CLASS : Aerosol Paint
 MSDS NUMBER : 20101

MANUFACTURER:	24 HOUR EMERGENCY:
DAP INC.	TRANSPORTATION: 1-800-535-5053
2400 BOSTON STREET	MEDICAL : 1-800-327-3874
BALTIMORE, MD 21224	

PREPARE DATE : 03/17/98	GENERAL INFORMATION:
REVISION NO. : 10	DAP INC.: 1-800-543-3840
REVISION DATE: 03/17/98	

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % RANGE
01	N-butane	106-97-8	10.0-20.0 %
02	Toluene	108-88-3	3.0-20.0 %
03	Titanium dioxide	13463-67-7	0.0-15.0 %
04	Petroleum naphtha,heavy alkylate	64741-65-7	1.0-20.0 %
05	Aliphatic Petroleum Distillate	64742-89-8	1.0-5.0 %
06	Acetone	67-64-1	10.0-35.0 %
07	Propane	74-98-6	10.0-20.0 %
08	Mineral spirits	8052-41-3	1.0-10.0 %
09	Calcium Carbonate	1317-65-3	1.0-5.0 %
10	Hydrous Magnesium Silicate	14807-96-6	5.0-20.0 %
11	Xylene	1330-20-7	1.0-10.0 %
12	Methyl Propyl Ketone	107-87-9	1.0-5.0 %
13	Methyl Isobutyl Ketone	108-10-1	1.0-5.0 %
14	Trimethylbenzene	25551-13-7	1.0-5.0 %
15	Aromatic hydrocarbon	64742-95-6	5.0-10.0 %
16	Methyl Ethyl Ketone	78-93-3	5.0-10.0 %

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

EXPOSURE LIMITS

ITEM	ACGIH		OSHA		COMPANY	
	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	SKIN
01	800 ppm	N.E.	800 ppm	N.E.	N.E.	NO
02	50 ppm.	N.E.	100 ppm.	N.E.	N.E.	YES
03	10 mg/m3dust	N.E.	10 mg/m3dust	N.E.	5 mg/m3dust	NO
04	300 ppm	N.E.	N.E.	N.E.	N.E.	NO
05	400 ppm	N.E.	400 ppm	N.E.	N.E.	NO
06	750 ppm	1000 ppm	750 ppm	N.E.	N.E.	NO
07	1000 ppm	N.E.	1000 ppm	N.E.	N.E.	NO
08	100 ppm	N.E.	100 ppm	N.E.	N.E.	NO
09	10 mg/m3	N.E.	15 mg/m3	N.E.	N.E.	NO
10	2 mg/m3	20 mg/m3	2 mg/m3	N.E.	N.E.	NO
11	100 ppm	150 ppm	N.E.	100 ppm	N.E.	NO
12	100 ppm	N.E.	200 ppm	N.E.	N.E.	NO
13	50 ppm	75 ppm	50 ppm	N.E.	N.E.	NO
14	25 ppm	N.E.	25 ppm	N.E.	N.E.	NO
15	400 ppm	N.E.	500 ppm	N.E.	N.E.	NO
16	200 ppm	300 ppm	200 ppm	N.E.	N.E.	NO

(See Section 16 for abbreviation legend), * - TLV-Ceiling Value

Remaining ingredients are not considered hazardous per the OSHA Hazard Communication Standard.

Listed Permissible Exposure Levels (PEL) are from the U.S. Dept. of Labor OSHA Final Rule Limits (CFR 29 1910.1000); limits may vary between states.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: DANGER! Extremely flammable liquid and vapor. Vapor may cause flash fire. Vapor harmful. Harmful or fatal if swallowed. Contents under pressure. Vapor harmful if inhaled. Exposure to temperatures above 120 degrees F. may cause can to rupture.

POTENTIAL HEALTH EFFECTS:

EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause eye irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: May irritate skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

SECTION 3 - HAZARDS IDENTIFICATION

EFFECTS OF OVEREXPOSURE - INHALATION: Vapor harmful if inhaled. Vapor may cause nose and throat irritation. Vapor inhalation may affect the brain or nervous system causing dizziness, headache or nausea. Inhalation of high concentrations of vapor is harmful and may lead to heart irregularities.

EFFECTS OF OVEREXPOSURE - INGESTION: This material may be harmful or fatal if swallowed. Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis which can be fatal. If ingested, this product may cause vomiting, diarrhea, and depressed respiration.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Reports have associated permanent brain and nervous system damage with prolonged and repeated occupational overexposure to solvents. Overexposure or misuse of toluene and xylene can cause liver, kidney, and brain damage as well as cardiac abnormalities. Symptoms include: loss of memory, loss of intellectual ability, and loss of coordination.

MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY CONTACT: If dry sanded, asthma and asthma-like conditions may worsen from prolonged or repeated exposure to dust.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT INHALATION

SECTION 4 - FIRST AID MEASURES

EYE CONTACT: Flush with large quantities of water until irritation subsides.

SKIN CONTACT: Wash with soap and water.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

INGESTION: DO NOT INDUCE VOMITING.

COMMENTS: Call Medical in Section 1 if irritation or complications arise from the above routes of exposure.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: Aerosol. Extremely flammable. LOWER EXPLOSIVE LIMIT: N.A.
UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE: N.E.

SECTION 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: CO2 DRY CHEMICAL FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS: Containers may explode if exposed to extreme heat. Eliminate sources of ignition: heat, electrical equipment, sparks, and flames. Do not put in contact with oxidizing or caustic materials.

SPECIAL FIREFIGHTING PROCEDURES: Full protective equipment, including self-contained breathing apparatus, is recommended to protect from combustion products. Cool exposed containers with water.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Use absorbent material or scrape up dried material and place into containers.

SECTION 7 - HANDLING AND STORAGE

HANDLING INFORMATION: KEEP OUT OF REACH OF CHILDREN. Avoid skin and eye contact. Avoid breathing vapors. Use only in a well ventilated area. Make sure nozzle arrow is directed away from yourself prior to discharge.

STORAGE INFORMATION: Store away from caustics and oxidizers. Keep away from heat, spark, and flame. Keep containers tightly closed when not in use. Keep containers from excessive heat and freezing. Do not store temperatures above 120 degrees F.

OTHER PRECAUTIONS: Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal. Do not take internally.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide sufficient mechanical ventilation (local or general exhaust) to maintain exposure below PEL and TLV. Vapors are heavier than air and will collect in low areas. Check all low areas (basements, sumps, etc.) for vapors before entering.

RESPIRATORY PROTECTION: If 8 hour exposure limit or value is exceeded for any component, use an approved NIOSH respirator. Consult your safety equipment supplier and the OSHA regulation, 29 CFR 1910.134 for respirator requirements. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: Goggles or safety glasses with side shields.

SKIN PROTECTION: Solvent impervious gloves.

OTHER PROTECTIVE EQUIPMENT: None.

HYGIENIC PRACTICES: Remove contaminated clothing and wash before reuse.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE	: N.A.	VAPOR DENSITY	: Is heavier than air
ODOR	: Gasoline-like		
APPEARANCE	: Various colors	EVAPORATION RATE:	Is faster than Butyl Acetate
SOLUBILITY IN H2O	: Negligible		
SPECIFIC GRAVITY	: 0.60-0.90		
VAPOR PRESSURE	: N.A.		
PHYSICAL STATE	: Liquid		

(See Section 16 for abbreviation legend)

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Excessive heat and freezing.

INCOMPATIBILITY: Strong oxidizers and caustics.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e. COx, NOx

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL PROPERTIES

No product or component toxicological information is available.

SECTION 12 - ECOLOGICAL INFORMATION

No Information.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE MANAGEMENT/DISPOSAL: Dispose of according to Federal, State, and Local Standards. Use all material before disposal. If unable to use entire contents of can, relieve pressure in container until it equals external pressure. Incineration of this can without first relieving all pressure may result in an explosion and personal injury. Responsibility for proper waste disposal is with the owner of the waste.

EPA WASTE CODE - If discarded (40 CFR 261): D001-Ignitable(if residue remains).

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: Consumer Commodity*

DOT HAZARD CLASS: ORM-D*

DOT UN/NA NUMBER: NONE* PACKING GROUP: NONE* RESP. GUIDE PAGE: 171

* For aerosol containers of 13 Fl. Oz. or less.

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME -----	CAS NUMBER	WT/WT % RANGE
Toluene	108-88-3	3.0-20.0 %
Xylene	1330-20-7	1.0-10.0 %
Methyl Isobutyl Ketone	108-10-1	1.0-5.0 %
Methyl Ethyl Ketone	78-93-3	5.0-10.0 %

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME ----- CAS NUMBER
No information is available.

SECTION 15 - REGULATORY INFORMATION

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

----- CHEMICAL NAME -----	CAS NUMBER
Alkyd Resin	TSRN-MWT00094

PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

----- CHEMICAL NAME -----	CAS NUMBER
Alkyd Resin	proprietary

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause birth defects or other reproductive harm:

----- CHEMICAL NAME -----	CAS NUMBER
Toluene	108-88-3

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: Consumer Commodity sold in retail market.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 2 FLAMMABILITY: 4 REACTIVITY: 1

PREVIOUS MSDS REVISION DATE: 02/01/97

Products that are classified as nonflat coatings contain a maximum of 65% VOC by weight.

Products that are classified as flat coatings contain a maximum of 60% VOC by weight.

Products that are classified as primers contain a maximum of 60% VOC by weight.

Products that are classified as clear coating contains a maximum of 67% VOC by weight.

SECTION 16 - OTHER INFORMATION

Changes that were made:

1. Consolidated Material Safety Data Sheets into one.
2. Added UPC#s, Medical Information in Section 1.
3. Added additional hazardous ingredients in Section 2.
4. Added xylene in chronic statement in Section 3.
5. Added Medical reference in Section 4.
8. Added additional VOC statements in Section 16.

LEGEND: ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS
N.A. - NOT APPLICABLE
N.E. - NOT ESTABLISHED
PEL - PERMISSIBLE EXPOSURE LIMIT
NTP - NATIONAL TOXICOLOGY PROGRAM
SARA - SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986
STEL - SHORT TERM EXPOSURE LIMIT
TLV - THRESHOLD LIMIT VALUE(8 HR. TIME WEIGHTED AVERAGE OR TWA)
VOC - VOLATILE ORGANIC COMPOUND
NJRTK - NEW JERSEY RIGHT TO KNOW LAW
N.D. - NOT DETERMINED

Supersedes MSDS# 20101 Revision 9, MSDS# 20201 Revision 11, MSDS# 20170
Revision 0, MSDS# 20801 Revision 7

This data is offered in good faith as typical values and not as a product specification. No warranty either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review the recommendations in specific context of the intended use and determine if they are appropriate.

< End OF MSDS >