

Material Safety Data Sheet

[\[Home\]](#) [\[Manufacturer\]](#) [\[Part Number\]](#) [\[NSN\]](#) [\[Help\]](#)

SECTION I - Material Identity

Item Name..... BLACK JACK FBRD ROOF CMNT .6230
 Part Number/Trade Name..... BLACK JACK FBRD PLASTIC ROOF
 CEMENT .6230
 National Stock Number..... 5610P6230
 CAGE Code..... 33394
 Part Number Indicator..... B
 MSDS Number..... 182023
 HAZ Code..... B

SECTION II - Manufacturer's Information

Manufacturer Name..... GIBSON-HOMANS COMPANY
 P.O. Box..... N/R
 Street..... 1755 ENTERPRISE PARKWAY
 City..... TWINSBURG
 State..... OH
 Country..... US
 Zip Code..... 44087
 Emergency Phone..... DAY:216/425-3253 NOC:216-467-8128
 Information Phone..... N/R

MSDS Preparer's Information

MSDS Preparer Name..... N/R
 Street..... 1755 ENTERPRISE PARKWAY
 City..... TWINSBURG
 State..... OH
 Zip Code..... 44087
 Date MSDS Prepared/Revised..... NONE
 Active Indicator..... N

Alternate Vendors

Vendor #1 Name..... N/R
 Vendor #1 CAGE..... N/R
 Vendor #2 Name..... N/R
 Vendor #2 CAGE..... N/R
 Vendor #3 Name..... N/R
 Vendor #3 CAGE..... N/R
 Vendor #4 Name..... N/R
 Vendor #4 CAGE..... N/R
 Vendor #5 Name..... N/R
 Vendor #5 CAGE..... N/R

SECTION III - Physical/Chemical Characteristics

Specification Number..... N/R
 Specification Type/Grade/Class..... N/R
 Appearance/Odor..... COURSE BLACK LIQUID, SOLVENT ODOR
 Boiling Point..... 300-315 F
 Melting Point..... N/A
 Vapor Pressure..... 25 DEG C.
 Vapor Density..... > 1
 Specific Gravity..... 1.1
 Decomposition Temperature..... N/R
 Evaporation Rate..... < 1/BUAC=1
 Solubility in Water..... NIL
 Percent Volatiles by Volume..... 10-30%
 Chemical pH..... N/R
 Corrosion Rate..... N/R
 Container Pressure Code..... 4
 Temperature Code..... 8
 Product State Code..... U

SECTION IV - Fire and Explosion Hazard Data

Flash Point Method..... PMCC
 Lower Explosion Limit..... .8
 Upper Explosion Limit..... 7.0
 Extinguishing Media..... FOAM, CARBON DIOXIDE, DRY CHEMICALS.

Special Fire Fighting Procedures..... THE USE OF SCBA IS RECOMMENDED FOR
FIREFIGHTERS. WATER MAY CAUSE
FROTHING. APPLY CAUTIOUSLY.

Unusual Fire/Explosion Hazards..... KEEP AWAY FROM SOURCES OF IGNITION.

SECTION V - Reactivity Data

Stability..... YES

Stability Conditions to Avoid..... HEAT, SPARKS, FLAMES

Materials to Avoid..... STRONG OXIDIZERS

Hazardous Decomposition Products..... CARBON DIOXIDE, CARBON MONOXIDE

Hazardous Polymerization..... NO

Polymerization Conditions to Avoid..... WILL NOT OCCUR

LD50 - LD50 Mixture..... N/R

SECTION VI - Health Hazard Data

Route of Entry: Skin..... YES

Route of Entry: Ingestion..... YES

Route of Entry: Inhalation..... YES

Health Hazards - Acute and Chronic..... CHRONIC: NONE KNOWN. ACUTE: SKIN-
PROLONGED/REPEATED CONTACT MAY CAUSE
IRRITATION. EYES: MAY CAUSE
IRRITATION, BLURRED VISION.
INHALATION: EXCESS. BREATHING OF
HIGH CONCENTRATIONS CAN CAUSE NASAL
AND RESPIR. IRRIT., DIZZINESS,
NAUSEA, POSS. UNCONCIOUSNESS

Carcinogenity: NTP..... NR

Carcinogenity: IARC..... NR

Carcinogenity: OSHA..... NR

Symptoms of Overexposure..... (SEE HEALTH HAZARDS ACUTE &
CHRONIC)- INGESTION CAN CAUSE
GASTROINTESTINAL IRRITATION, NAUSEA,
VOMITING AND DIARRHEA.

Medical Cond. Aggrevated by Exposure.... PRE-EXISTING LUNG AND SKIN DISORDERS.

Emergency/First Aid Procedures..... SKIN: WASH W/SOAP & WATER. EYES:
FLUSH W/LARGE AMOUNTS OF WATER.
INHALATION: REM

SECTION VII - Precautions for Safe Handling and Use

Steps if Material Released/Spilled..... DIKE SPILL AREA. RECOVER FREE LIQUID. ADD ABSORBENT TO SPILL AREA. REMOVE SOURCES OF IGNITION. VENTILATE AREA IF NECESSARY.

Neutralizing Agent..... NONE REPORTED.

Waste Disposal Method..... DISPOSE OF ACCORDING TO FEDERAL, STATE AND LOCAL REGULATIONS.

Handling and Storage Precautions..... KEEP AWAY FROM SOURCES OF IGNITION. USE ONLY WITH ADEQUATE VENTILATION. AVOID PROLONGED/REPEATED CONTACT WITH SKIN.

Other Precautions..... KEEP OUT OF REACH OF CHILDREN.

SECTION VIII - Control Measures

Respiratory Protection..... NOT NORMALLY NEEDED IN WELL VENTILATED AREA. IF TLV IS EXCEEDED, A NOISH/MESA APPROVED BREATHING APPARATUS IS RECOMMENDED.

Ventilation..... AS NECESSARY TO MAINTAIN EXPOSURE BELOW TLV LEVEL

Protective Gloves..... SOLVENT RESISTANT

Eye Protection..... CHEMICAL GOGGLES

Other Protective Equipment..... AS NECESSARY.

Work Hygenic Practices..... REMOVE CONTAMINATED CLOTHING. LAUNDRER BEFORE REUSE.

Supplemental Health/Safety Data..... 1ST AID: SKIN WASH W/SOAP & WATER. EYES: FLUSH W/LARGE AMOUNTS OF WATER. INHALATION: REMOVE PERSON FROM AFFECTED AREA. IF BREATHING IS DIFFICULT ADMIN. OXYGEN. IF BREATHING HAS STOPPED GIVE ARTIF. RESPIR. INGEST.: DO NOT INDUCE VOMITING. SEEK MEDICAL ATTN.

SECTION IX - Label Data

Protect Eye..... YES

Protect Skin..... YES

Protect Respiratory..... YES

Chronic Indicator..... UNKNOWN

Contact Code..... MODERATE

Fire Code..... UNKNOWN

Health Code..... UNKNOWN
React Code..... UNKNOWN

SECTION X - Transportation Data

Container Quantity..... 5
Unit of Measure..... GL

SECTION XI - Site Specific/Reporting Information

SECTION XII - Ingredients/Identity Information

Ingredient #..... 01
Ingredient Name..... MINERAL SPIRITS
CAS Number..... 8052413
NIOSH Number..... NR
Proprietary..... NO
Percent..... 15-40%
OSHA PEL..... 100 PPM
ACGIH TLV..... 100 PPM/525 MG/M3
Recommended Limit..... N/R

NOTICE: For additional information, contact BIOENVIRONMENTAL

HMMS Intranet - 13 Sep 2006 09:49 - web_msdms.display - Visit the Official HMMS Website at www.hmms.com