

10/03

Jeld-Wen Coatings
1061 Industry Dr.
Tukwila, WA 98188

Date: February 11, 2002
Telephone No: (206) 574-0987

MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT IDENTIFICATION:

TRADE NAME:.....JW-04-014 Gladiator Challenge Dooredge Primer
MANUFACTURER:.....Jeld-Wen Coatings-1061 Industry Dr. Tukwila, WA 98188
CHEMICAL FAMILY:.....Water Reducible Primer.
DOT SHIPPING NAME:.....Acrylic Polymer product in water.
DOT LD. NUMBER.....Nonregulated

SECTION 2 HAZARDOUS INGREDIENTS:

Ingredients	CAS NO.	OSHA PEL	ACGIH TLV	OSHA STEL	APPROX %
Dipropylene Glycol Monomethyl Ether	34590-94-8	Unknown	Unknown	Unknown	0-2 %

This MSDS complies with the OSHA Hazard Communication Standard(29 CFR 19190.1200). Unlisted ingredients are not 'Hazardous' per this OSHA Standard and are considered to be trade secrets of Jeld-Wen Coatings.. Consult Section 12 for the nature of the hazard(s).

SECTION 3 PRECAUTIONARY INFORMATION:

Product not considered hazardous under normal conditions. Direct contact of product with eyes.. can cause irritation. Prolonged or repeated contact with skin may cause irritation.

SECTION 4 EMERGENCY AND FIRST AID PROCEDURES:

FIRST AID:

EYE: Flush immediately with water for 15 minutes. Consult a physician if irritation persists.

SKIN: Wash affected area with soap and water. Wash contaminated clothing before reuse.

INHALED: Remove subject to fresh air.

FIRE: Product is non-flammable in the liquid state. Use water spray, foam, dry chemical or carbon dioxide on dried product.

MATERIAL SAFETY DATA SHEET

Jeld-Wen Coatings

1061 Industry Dr.

Tukwila, WA 98188

JW-04-014

Date: February 11, 2002

Telephone No: (206) 574-0986

SPILL: Collect and remove using inert absorbent. Contain spill to prevent entering sewers. Notify appropriate agencies.

SECTION 5 PERSONAL PROTECTION EQUIPMENT:

EYE: Wear chemical safety goggles to reduce the potential for eye contact. Eye wash fountain should be available

SKIN: Use impermeable chemical gloves and wear appropriate protective clothing. Launder contaminated clothing before reusing.

Respiratory: Respiratory protection is not normally required. Use NIOSH/MSHA approved respirator if conditions warrant.

Ventilation: Standard industrial ventilation is recommended.

SECTION 6 FIRE PROTECTION

Flash Point: N/A

Extinguishing Media:

Non-flammable in liquid state; use water spray, foam, dry chemical. Use carbon dioxide on dried product.

Unusual Fire and Explosion Hazard

Personnel exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.

Containers exposed in a fire should be cooled with water to prevent vapor pressure buildup leading to a rupture.

SECTION 7 REACTIVITY INFORMATION:

Stability: Stable.

Incompatibility:

Not Established

Hazardous Decomposition Products:

Combustion of the dried product can yield low molecular weight hydrocarbons such as carbon monoxide and carbon dioxide.

Hazardous Polymerization:

Will not occur.

MATERIAL SAFETY DATA SHEET

Jeld-Wen Coatings
1061 Industry Dr. Tukwila, WA 98188

JW-04-014

Date: February 11, 2002
Telephone No: (206) 574-0986

SECTION 8 EFFECT OF OVEREXPOSURE:

Eyes: Eye contact with liquid may cause irritation.

Skin: Repeated or prolonged skin contact with liquid may cause irritation.

Inhalation: No expected effects.

Chronic: No anticipated effects.

This product does not contain regulated levels of NTP, IARC or OSHA listed carcinogens.

Existing Health Conditions Affected By Exposure:
No known effects on other illnesses.

SECTION 9 PHYSICAL DATA:

Physical State: Liquid
Weight/Gallon: 14.10 Lbs.
Viscosity: 30-35 seconds # Zahn cup
Solids: 70.0 % by Weight.
pH: 8.5-9.5
Boiling Point: > 200°F.
Flash Point: N/A
Solubility in Water: Dilutable

SECTION 10 SPILL AND DISPOSAL INFORMATION:

SPILL OR LEAK PROCEDURES:

Small Spills- should be contained using absorbent material, such as clay, soil or any commercially available absorbent. Shovel reclaimed liquid and absorbent into recovery or salvage drums for disposal.

Large Spills- Should be diked to prevent further movement and reclaim into recovery or salvage drums for disposal.

Disposal: This product *does not* meet the definition of *hazardous waste* under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Consult your state or local authorities for proper disposal in the event more restrictive requirements apply.

MATERIAL SAFETY DATA SHEET

Jeld-Wen Coatings

1061 Industry Dr.

Tukwila, WA 98188

JW-04-014

Date: February 11, 2002

Telephone No: (206) 574-0986

SECTION 11 STORAGE:

Protect from freezing- product stability may be affected.

SECTION 12 ENVIRONMENTAL INFORMATION:

TOSCA This product meets the compositional requirements under the regulations of the Chemical Substance Inventory, TOSCA, Public Law 94-469.

SARA TITLE III, SECTION 313:

This product does not contain toxic chemical(s) at or above the de minimus concentrations subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARS) and 40 CFR part 372.

<u>CHEMICAL NAME</u>	<u>CAS NUMBER</u>	<u>PERCENT</u>
NA	NA	NA

Weight per gallon: 14.10 lbs.**VOC Content: 0.28 lb/gallon****Weight Solids: 70.00%****Photochemically Reactive: No**

Volatile Ingredients	Sara 302 EHS	CERC	SARA 313	HAPS	Weight %
Dipropylene Glycol	No	No	Yes	No	1.8
Water	No	No	No	No	21.8

MATERIAL SAFETY DATA SHEETS

Jeld-Wen Coatings
1061 Industry Dr. Tukwila, WA 98188

JW-04-014

Date: Febuary 11, 2002
Phone: (206)574-0986

ABBREVIATIONS:

NA- not applicable, NE- not established, NSR- no special requirement, ND- not determined.

Jeld-Wen Coatings believes that the information provided is accurate and reliable as of the date of this material safety data sheet and is given in good faith. No warranty expressed or implied is made as to the accuracy, reliability, or completeness of the information. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State and Local laws and regulations. Jeld-Wen Coatings urges persons receiving this information to make their own determination as to the information's suitability and applicability for an intended use.

NOTE: This information must be included in all MSDS that are copied and distributed for this material.

JW-04-014 Gladiator Challenge Dooredge Primer
02/11/02

Jeld-Wen Coatings
1061 Industry Dr.
Tukwila, WA 98188
(206) 574-0986