



View Section: [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [11](#) [12](#) [13](#) [14](#) [15](#) [16](#)

**SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

Product Name: **KILZ® Original**  
Product Number: 1000  
Manufacturer Name: Masterchem Industries LLC  
Address: 3135 Old Highway M  
Imperial MO 63052-2834

U.S. Contact Info.:

Business Phone: (636) 942-2510  
Technical Service Phone: (800) 325-3552  
Business Fax: (636) 942-3663


Canadian Contact Info.:

Business Phone: (800) 661-1591  
Technical Service Phone: (800) 661-1591  
Business Fax: (403) 273-1128

**For emergencies in the US, call CHEMTREC: 800-424-9300**

**In Canada, call CANUTEC: (613) 996-6666 (call collect)**

**NFPA**



**HMIS**

<b>HEALTH</b>	<b>1</b>
<b>FIRE</b>	<b>3</b>
<b>REACTIVITY</b>	<b>0</b>
<b>PPE</b>	

[To Top of page](#)

**SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS**

Product No.  
1000

<b>Chemical Name</b>	<b>CAS#</b>	<b>Lower Percent</b>	<b>Upper Percent</b>
Silicate, mica	12001-26-2	10	30
VM&P Naphtha/Aliphatic Hydrocarbon	8032-32-4	10	30
Titanium dioxide	13463-67-7	5	10
Rutile	1317-80-2	5	10
Nepheline Syenite	37244-96-5	1	5
Octanes, all isomers	Mixture	1	5
Petroleum hydrocarbon distillates	8052-41-3	1	5
Heavy Hydrotreated Naphtha (Petroleum)	64742-48-9	1	5
Light Hydrotreated Distillate (Petroleum)	64742-47-8	1	5
Talc, Magnesium silicate hydrate	14807-96-6	1	5
Xylene	1330-20-7	0.1	1
Non-hazardous ingredients		10	30
Nonane, all isomers	Mixture	5	10

[To Top of page](#)

**SECTION 3: HAZARDS IDENTIFICATION**

Product No.  
1000

**Emergency Overview:** Flammable. Irritant.

**Applies to all Ingredients**

**Potential Health Effects:**

- Eye Contact:** May cause irritation.
- Skin Contact:** May cause irritation.
- Skin Absorption:** May be absorbed through the skin in harmful amounts.
- Inhalation:** Prolonged or excessive inhalation may cause respiratory tract irritation.
- Ingestion:** Harmful if swallowed. Ingestion can cause nausea, vomiting, diarrhea and gastrointestinal irritation.
- Chronic Skin Contact:** Prolonged or repeated contact can result in defatting and drying of the skin, which may result in skin irritation and dermatitis (rash).
- Chronic Inhalation:** Repeated or prolonged inhalation may cause toxic effects.
- Target Organs:** Eyes. Skin. Respiratory system. Digestive system. Central nervous system. Kidney.
- Signs/Symptoms:** Overexposure can cause headaches, dizziness, nausea, and vomiting.
- Aggravation of Pre-Existing Conditions:** May aggravate pre-existing respiratory disorders, allergy, eczema, or skin conditions.

[To Top of page](#)

---

## SECTION 4: FIRST AID MEASURES

Product No.  
1000

Eye Contact:	Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention, if irritation or symptoms of overexposure persists.
Skin Contact:	Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.
Other First Aid:	Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have the person lean forward to reduce the risk of aspiration.

[To Top of page](#)

---

## SECTION 5: FIRE FIGHTING MEASURES

Product No.  
1000

Fire:	Flammable liquid.
Flash Point:	75°F (24.9°C)
Flash Point Method:	SETA
Upper Flammable or Explosive Limit:	7%
Lower Flammable or Explosive Limit:	1%
Extinguishing Media:	Use alcohol foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.
Fire Fighting Instructions:	Flammable. Cool fire-exposed containers using water spray.
Protective Equipment:	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Unusual Fire Hazards:	Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back.

[To Top of page](#)

---

## SECTION 6: ACCIDENTAL RELEASE MEASURES

Product No.  
1000

Personal Precautions:	Use proper personal protective equipment as listed in section 8.
Spill Cleanup Measures:	Remove all sources of ignition. Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Collect spill with a non-sparking tool. Place into a suitable container for disposal.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.

[To Top of page](#)

---

## SECTION 7: HANDLING AND STORAGE

Product No.  
1000

<b>Handling:</b>	Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper grounding procedures.
<b>Storage:</b>	Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in use.
<b>Work Practices:</b>	To reduce potential for static discharge, bond and ground containers when transferring material.
<b>Hygiene Practices:</b>	Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.
<b>Special Handling Procedures:</b>	Do not reuse containers without proper cleaning or reconditioning.
<b>Important Storage and Disposal:</b>	<b>DANGER!</b> Rags, steel wool and waste soaked with this product may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container. Do not store unused product inside the home. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency.

[To Top of page](#)

---

## SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

Product No.  
1000

<b>Engineering Controls:</b>	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
<b>Skin Protection Description:</b>	Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.
<b>Hand Protection Description:</b>	Wear appropriate protective gloves. Consult glove manufacturer's data for permeability data.
<b>Eye/Face Protection:</b>	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
<b>Respiratory Protection:</b>	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

**Other Protective:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

<b>Ingredient Guidelines</b>	<b>Guideline Type</b>	<b>Guideline Information</b>
<b>Light Hydrotreated Distillate (Petroleum)</b>		
	ACGIH TLV-TWA	200 mg/m3 (Negligible aerosol exposures)
<b>Petroleum hydrocarbon distillates</b>		
	ACGIH TLV-TWA	100 ppm
	OSHA PEL-TWA	500 ppm
<b>Silicate, mica</b>		
	OSHA PEL-TWA	20 mg/m3
	ACGIH TLV-TWA	3 mg/m3 (Respirable)
<b>Talc, Magnesium silicate hydrate</b>		
	OSHA PEL-TWA	20 mg/m3
	ACGIH TLV-TWA	2 mg/m3 (Respirable)
<b>Titanium dioxide</b>		
	ACGIH TLV-TWA	10 mg/m3
	OSHA PEL-TWA	15 mg/m3
<b>VM&amp;P Naphtha/Aliphatic Hydrocarbon</b>		
	ACGIH TLV-TWA	300 ppm
<b>Xylene</b>		
	OSHA PEL-TWA	100 ppm
	ACGIH TLV-TWA	100 ppm
	ACGIH TLV-STEL	150 ppm

[To Top of page](#)

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Product No.  
1000

Physical State/Appearance: Liquid  
 pH: No Data  
 Vapor Density: Greater than 1 (Air = 1)  
 Density: 10 - 12 Lbs./gal.  
 Molecular Formula: Mixture  
 Molecular Weight: Mixture  
 Flash Point: 75°F (24.9°C)

VOC: Material VOC: 444gm/l (Includes Water)"  
"Coating VOC: 444 gm/l (Excludes Water)

[To Top of page](#)

---

## SECTION 10: STABILITY AND REACTIVITY

Product No.  
1000

Chemical Stability: Stable under normal temperatures and pressures.  
Conditions to Avoid: Heat, flames, ignition sources, and sparks. Incompatible materials. Freezing or temperatures below 32 deg. F.  
Incompatibilities with Other Materials: Oxidizing agents. Strong acids and alkalis.  
Hazardous Polymerization: Not reported.  
Hazardous Decomposition Products: Incomplete combustion may produce carbon monoxide and other toxic gases.  
Note: Refer to Section 7

[To Top of page](#)

---

## SECTION 11: TOXICOLOGICAL INFORMATION

Product No.  
1000

### Petroleum hydrocarbon distillates

Eye Effect: Eye - Rabbit; Standard Draize : 500 mg/24H; Moderate. (RTECS)  
Ingestion Effects: Ingestion - Rat LD: >5 gm/kg; Behavioral - somnolence (general depressed activity) (RTECS)  
Inhalation Effects: Inhalation - Rat LCLo: 8200 mg/m<sup>3</sup>/8H; Behavioral - tremor  
Inhalation - Rat LC: >5500 mg/m<sup>3</sup>/4H; Behavioral - somnolence (general depressed activity) (RTECS)

### VM&P Naphtha/Aliphatic Hydrocarbon

Eye Effect: Eye's - Human: 880 ppm/15M; No effects reported. (RTECS)

### Talc, Magnesium silicate hydrate

Carcinogenicity: IARC: Group 3: Unclassifiable as to carcinogenicity to humans

### Titanium dioxide

Skin Effects: Skin - Rabbit; Standard Draize : 300 ug/3D; (Intermittent) Mild. (RTECS)  
Ingestion Effects: Ingestion - Rat TDLo: 60 gm/kg; Gastrointestinal - hypermotility, diarrhea  
Gastrointestinal - other changes. (RTECS)

Carcinogenicity: IARC: Group 3: Unclassifiable as to carcinogenicity to humans

### Xylene

Eye Effect: Eye - Rabbit; Standard Draize : 87 mg; Mild.  
Eye - Rabbit; Standard Draize : 5 mg/24H; Severe. (RTECS)

Skin Effects: Skin - Rabbit; Standard Draize : 100%; Moderate.  
Skin - Rabbit; Standard Draize : 500 mg/24H; Moderate. (RTECS)

Ingestion Effects: Ingestion - Rat LD50: 4300 mg/kg; Liver - other changes Kidney, Ureter, Bladder - other changes  
Ingestion - Mouse LD50: 2119 mg/kg; Details of toxic effects not reported other than lethal dose value (RTECS)

**Inhalation Effects:** Inhalation - Rat LC50: 5000 ppm/4H; Details of toxic effects not reported other than lethal dose value (RTECS)

**Carcinogenicity:** IARC: Group 3: Unclassifiable as to carcinogenicity to humans

**Notes** Not all of the toxicological studies for the ingredients contained in this product are displayed. For additional information, please consult the references listed in Section 16 of this MSDS.

[To Top of page](#)

---

## SECTION 12: ECOLOGICAL INFORMATION

Product No.  
1000

**Ecotoxicity:** No ecotoxicity data was found for the product.

**Environmental Fate:** No environmental information found for this product.

[To Top of page](#)

---

## SECTION 13: DISPOSAL CONSIDERATIONS

Product No.  
1000

**Waste Disposal:** Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

**Important Disposal Information:** DANGER! Rags, steel wool and waste soaked with this product may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container. Do not store unused product inside the home. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency.

[To Top of page](#)

---

## SECTION 14: TRANSPORT INFORMATION

Product No.  
1000

**DOT Shipping Name:** Paint.

**DOT UN Number:** UN1263

**DOT Hazard Class:** 3

**DOT Identification Number:** UN1263

**DOT Packing Group:** II

[To Top of page](#)

**SECTION 15: REGULATORY INFORMATION**

Product No.  
1000

**Heavy Hydrotreated Naphtha (Petroleum)**

TSCA 8(b): Inventory Status: Listed

Canada DSL: Listed

**Light Hydrotreated Distillate (Petroleum)**

TSCA 8(b): Inventory Status: Listed

Canada DSL: Listed

**Nepheline Syenite**

TSCA 8(b): Inventory Status: Not listed

Canada DSL: Listed

**Non-hazardous ingredients**

TSCA 8(b): Inventory Status: Contains calcium carbonate (CAS: 1317-65-3), which is listed in the TSCA inventory.

**Petroleum hydrocarbon distillates**

TSCA 8(b): Inventory Status: Listed

State: Listed in the New Jersey State Right to Know list.  
Listed in the Pennsylvania Hazardous Substances list.

Canada DSL: Listed

**Rutile**

TSCA 8(b): Inventory Status: Listed

State: Listed in the Pennsylvania Hazardous Substances list.

Canada DSL: Listed

**Silicate, mica**

TSCA 8(b): Inventory Status: Not listed

State: Listed in the New Jersey State Right to Know list.  
Listed in the Pennsylvania Hazardous Substances list.

Canada DSL: Listed

**VM&P Naphtha/Aliphatic Hydrocarbon**

TSCA 8(b): Inventory Status: Listed

State: Listed in the New Jersey State Right to Know list.  
Listed in the Pennsylvania Hazardous Substances list.

Canada DSL: Listed

**Talc, Magnesium silicate hydrate**

TSCA 8(b): Inventory Status: Listed

State: Listed in the New Jersey State Right to Know list.  
Listed in the Pennsylvania Hazardous Substances list.

Canada DSL: Listed

**Titanium dioxide**

TSCA 8(b): Inventory Status: Listed

State: Listed in the New Jersey State Right to Know list.  
Listed in the Pennsylvania Hazardous Substances list.

Canada DSL: Listed



## Xylene

**TSCA 8(b): Inventory Status:** Listed  
**State:** Listed in the New Jersey State Right to Know list.  
Listed in the Pennsylvania Hazardous Substances list.  
**Canada DSL:** Listed

[To Top of page](#)

---

## SECTION 16: ADDITIONAL INFORMATION

Product No.  
1000

---

**MSDS Revision Date:** "06/26/2006"  
**MSDS Author:** Actio Corporation  
**Disclaimer:**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific materials designated. Refer to individual product safety Data sheets when using more than one product in combination with another.

### References:

1. OSHA Hazard Communication Standard, 1910.1200 and Z Tables.
2. NIOSH Registry of Toxic Effects of Chemical Substances (RTECS) and Pocket Guide to Chemical Hazards.
3. Sax Dangerous Properties of Industrial Materials. Tenth Edition.
4. Hawleys Condensed Chemical Dictionary, Thirteenth Edition
5. IARC monographs on the Evaluation of the Carcinogenic Risk of Chemicals to Man, WHO International Research on Cancer, 2004.
6. Industrial Hygiene and Toxicology, by F.A. Patty.
7. National Library of Medicine, Department of Health and Human Services, Hazardous Substances Data Bank (HSDB).
8. National Toxicology Program (NTP) Tenth Report on Carcinogens, 2002.
9. Brethericks Reactive Chemical Hazards Database. Version 2.
10. Gassarett and Doulls Toxicology, The Basic Science of Poisons.
11. The Merck Index: An Encyclopedia of Chemicals and Drugs. Merck and Company. Twelfth Edition 1998.
12. Threshold Limit Values for Chemical Substances and Physical Agents in the Work Environmental and Biological Exposure Indices. TLV Booklet, 2003.

Copyright © 1996-2006 [Actio Software Corporation](#). All Rights Reserved.

The trademarks, service marks, graphics and logos used on this MSDS are registered or unregistered trademarks of MasterChem Corporation. All Rights Reserved.

[To Top of page](#)