

SAFETY DATA SHEET

PRODUCT NAME: WOOD STAIN (pigmented wiping stain)

PRODUCT CODE: M545/547/549-ALL M545a

HMIS CODES: H F R P 1 2 0 B

SECTION I - MANUFACTURER IDENTIFICATION
MANUFACTURER'S NAME: Mohawk Finishing Products, Inc.
ADDRESS : 4715 State Hwy 30
Amsterdam, New York 12010

GENERAL ID : OIL FINISH
DOT HAZARD CL. : COMBUSTIBLE LIQ
PACKING GRP. : III
UN/NA#/ERG : NA1993 G128

EMERGENCY PHONE: 518-843-1380
INFORMATION : 518-843-1380
DATE PRINTED: 09/29/97
SIGNATURE OF PREPARER : *Robert Martin*

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	%	OSHA PEL	ACGIH/TLV	MG/M3
PETROLEUM DISTILLATE	64742-95-6	>1			
PETROLEUM DISTILLATE	64742-94-5	>1	50 PPM	50 PPM	245
* XYLENE	1330-20-7	9	100 PPM	N/L	563
PETROLEUM DISTILLATE	64742-89-8	>1	100 PPM	100 PPM	434
			300 PPM	300 PPM	1800

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING PT. : 279F/137C
VAPOR PRES. : 9.5 MM
VAPOR DENSITY: >1.0 (AIR=1)
SOLUBILITY IN WATER: Negligible.
APPEARANCE AND ODOR: Colored liquid, mild odor.

SPECIFIC GRAVITY (Approx.) : 0.97
EVAPORATION RATE: <1.0 (B. Acetate=1)
METH. VOC : 748 g/l 6.24 lb/gal
HAP/LB SOLIDS: 0.38
MELTING PT: N/A

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH PT. : 100F/38C
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 0.9% UPPER: 7.0%
EXTINGUISHING MEDIA: Water spray, "alcohol" foam, dry chemical, foam, CO2, or any class B extinguishing agent.

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus when fighting fires in confined space. If water is used, fog nozzles are preferred.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air, may travel considerable distance to a source of ignition and flashback. Use water fog to cool containers to prevent rupturing.

SECTION V - REACTIVITY DATA

STABILITY: Yes
INCOMPATIBILITY (MATERIALS TO AVOID): oxidizing materials can cause a vigorous reaction.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Combustion will produce fumes, smoke, carbon dioxide, and probably carbon monoxide.
HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VI - HEALTH HAZARD DATA

HEALTH HAZARDS (ACUTE AND CHRONIC): Harmful if inhaled, may affect the brain or nervous system, causing dizziness, headache or nausea. Causes nose, throat, eye and skin irritation. Reports have associated repeated and prolonged occupational over-exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

CARCINOGENICITY: No
IARC MONOGRAPHS: N/L.
SUBJECT TO CA. PROPOSITION 65 REPORTING? CARCINOGEN: YES REPRODUCTIVE: YES
NTP CARCINOGEN: N/L.
OSHA REGULATED: N/L.
May contain trace amounts of chemicals known to the state of California to cause

MATERIAL SAFETY DATA SHEET

Pg 2 of 2

cancer and/or reproductive toxicity.

SIGNS AND SYMPTOMS OF EXPOSURE:

Breathing difficulty, light-headedness, dryness of respiratory tract.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Any medical condition, allergy, sensitization which may become worse upon exposure to the product.

EMERGENCY AND FIRST AID PROCEDURES: **IN EYES:** Flush immediately with large amounts of water for 15 minutes. Take to physician for treatment. **IF INHALED:** Remove to fresh air, restore breathing. Consult a physician. **IF ON SKIN:** Wash areas with soap and water. Remove contaminated clothing. Consult physician. **IF SWALLOWED:** Do not induce vomiting. Consult physician immediately.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Isolate, absorb and ventilate (open all windows, doors). Removal of all ignition sources, flames, hot surfaces. Avoid breathing of vapors, use respiratory protective device.

WASTE DISPOSAL METHOD:

In accordance with federal, state and local regulations. Before attempting clean-up, refer to hazard caution information in other sections of form.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Avoid high temperatures. Do not store or use near heat, sparks or flame. Prevent prolonged or repeated breathing of vapor or spray mist.

OTHER PRECAUTIONS: Do not take internally. Avoid prolonged contact with skin. **DO NOT GET IN EYES.** Avoid breathing of vapors or dust. **KEEP OUT OF REACH OF CHILDREN!** Follow label directions.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: If workplace exposure limit(s) of product or any component is exceeded, a NIOSH approved, organic vapor cartridge respirator is advised in absence of proper environmental control.

VENTILATION

LOCAL : Local exhaust not adequate.

MECHANICAL : Mechanical exhaust sufficient to prevent exceeding listed TLV. When unavailable, supplied air respiratory protection is recommended.

PROTECTIVE GLOVES: Neoprene gloves.

EYE PROTECTION: Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other types of safety glasses. Consult your safety representative.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: N/A.

WORK/HYGIENIC PRACTICES: Personal contact should be avoided. Follow good housekeeping and personal hygiene.

SECTION IX - DISCLAIMER

To the best of our knowledge the information contained herein is accurate. All information has been obtained from sources which Mohawk Finishing Products, Inc. believes to be accurate.