

B



**OLYMPIC
HOMECARE PROD CO**
2233-112TH AVENUE N.E., C-02233, BELLEVUE, WASHINGTON 98004
TELEPHONE (206) 453-1700

RECEIVED
Material Safety
Data Sheet

CLOROX-RMIS	
HEALTH	2*
FLAMMABILITY	2
REACTIVITY	1
Personal Protection	C

I Chemical Identification

NAME:	OLYMPIC WEATHER SCREEN SEMI-TRANSPARENT PRESERVATIVE OIL STAINS	CAS no.	N/A
DESCRIPTION:	THIN LIQUID, MILD ODOR, VARIOUS COLORED STAINS	RTECS no.	N/A
Other Designations	Manufacturer	Emergency Procedure	
EPA Reg. No. 7313-5 Color Nos. 704 705 707 708 709 711 712 713 716 717 718 723 725 726 727 730 901 908 910 911 913 916 919 920	The Olympic HomeCare Products Company 2233 112th Avenue Bellevue, WA 98004	Notify your Supervisor Call your local poison control center or Rocky Mountain Poison Center (303) 573-1014	

II Health Hazard Data

*Harmful or fatal if swallowed. Severe skin irritant upon prolonged contact. Slight eye irritant. Repeated or prolonged exposure to vapors may result in dizziness, headaches and/or unconsciousness. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful. No medical conditions are known to be aggravated by exposure to this product. Under normal consumer use conditions the likelihood of any adverse health effects are low. **FIRST AID: INGESTION: DO NOT** induce vomiting. Call a physician. **SKIN:** Remove contaminated clothing. Wash skin with soap and water. **INHALATION:** If breathing problems develop, remove from exposure. **EYE:** Flush immediately with water for at least 15 minutes. Call a physician.

III Hazardous Ingredients

Ingredients	Concentration	Worker Exposure Limits
Mineral Spirits	50-75%	50ppm TWA 100ppm TLY-TWA 500ppm PEL
CAS Nos: 67442-47-8, 64741-65-7, 64742-88-7		
Bis (tributyltin) Oxide	0.5%	not established
CAS# 56-35-9		
N-[(trichloromethyl)thio]	0.5%	not established
phthalimide	CAS# 133-07-3	
None of the materials in this product are on the IARC, NTP or OSHA carcinogen lists.		
TWA = Time Weighted Average. The 50ppm Worker Exposure Limit is recommended by The Clorox Co. based on review of toxicological data.		
TLY-TWA = Threshold Limit Value-Time Weighted Average. Source: ACGIH.		
PEL = Permissible Exposure Limit. Source: OSHA		

IV Special Protection Information

Hygienic Practices: Wear safety glasses, gloves and protective clothing. If you experience headaches, nausea or dizziness leave the area until symptoms cease. Increase fresh air or wear a properly fitted respirator (NIOSH/MSHA TC-23) with an organic vapor cartridge. Wear a dust respirator while sanding.

Engineering Controls: Use general ventilation (fan, open windows, doors) to keep the mineral spirits exposure level below the Worker Exposure Limit.

Work Practices: Minimize skin and eye contact and inhalation of vapor, mist and dust. Avoid inhalation of dust while sanding.

V Special Precautions

Keep out of reach of children. Avoid eye and skin contact and inhalation of vapor or mist. Avoid breathing dust while sanding. USE ONLY IN WELL VENTILATED AREA. Do not use or store near open flame. Do not drink alcohol while working with this product. Do not drive, operate machinery or climb ladders if you experience headaches, nausea or dizziness.

VI Spill or Leak Procedures

Extinguish all sources of ignition in vicinity of spill. Ventilate with non-rotating fan to release vapors. Clean up spills as soon as possible. Absorb spills with clay or diatomaceous earth. Dispose of in accordance with local, state and federal regulations.

VII Reactivity Data

Stable under normal use and storage conditions.

VIII Fire and Explosion Data

Flash Point = 105°F/41°C (TCC)
Flammable Limits: Lower = 11, Upper = 6%
Use foam, dry chemical, carbon dioxide or water spray as extinguishing material. To avoid spontaneous combustion of oily clothes and rags soak in water after use or place in a closed metal container away from building and other combustible material.

IX Physical Data

Boiling point-----315°F/157°C
Flash point (TCC)-----105°F/41°C
Solubility in water-----Insoluble
Vapor Density (Air=1)-----4.9
Vapor Pressure at 77°F-----2 mm Hg

0383H

©1983 THE CLOROX COMPANY

DATE PREPARED 10/87

CLOROX-HMIS	
HEALTH	2*
FLAMMABILITY	2
REACTIVITY	1
Personal Protection	c

I Chemical Identification

NAME: OLYMPIC WEATHER SCREEN SOLID COLOR PRESERVATIVE OIL STAINS **CAS no.** N/A
DESCRIPTION: THIN LIQUID, MILD OOR, VARIOUS COLORED STAINS **RTECS no.** N/A
Other Designations **Manufacturer** **Emergency Procedure**

EPA Registration No. 7313-8 Beechwood, Belize Gray, Butternut, Cal. Rustic Cape Cod Gray, Cedar, Chamels, Chocolate, Cocoa, Deep Charcoal, Ebony, Heritage Blue, Mahogany, Monterey Gray, Navajo Red, Navajo White, Outside White, Oxford Brown, Pewter, Pineset, Sandstone, Stonehedge, Taupe, Willow Mist	The Olympic HomeCare Products Company 2233 112th Avenue NE Bellevue, WA 98004	Notify your Supervisor Call your local poison control center or Rocky Mountain Poison Center (303) 573-1014
---	---	---

II Health Hazard Data

*Harmful or fatal if swallowed. Moderate skin irritant upon prolonged contact. Slight eye irritant. Repeated or prolonged exposure to vapors may result in dizziness, headaches and/or unconsciousness. Overexposure to magnesium silicate, which may occur while sanding, may cause permanent lung impairment. No medical conditions are known to be aggravated by exposure to this product. Under normal consumer use conditions the likelihood of any adverse health effects are low. See Section VIII for additional health information. **FIRST AID: INGESTION: DO NOT** induce vomiting. Call a physician. **SKIN:** Remove contaminated clothing. Wash skin with soap and water. **INHALATION:** If breathing problems develop, remove from exposure. **EYE:** Flush immediately with water for at least 15 minutes. Call a physician.

III Hazardous Ingredients

Ingredients	Concentration	Worker Exposure Limits
Mineral Spirits	25-50%	50ppm TWA
CAS Nos: 67442-47-8, 64741-65-7, 64742-88-7		100ppm TLV-TWA
Magnesium Silicate	10-40%	500ppm PEL
CAS# 14807-96-6		2mg/m ³ TLV-TWA
Bis (tributyltin) oxide	0.5%	not established
CAS# 56-35-9		
N-(trichloromethylthio) phthalimide CAS# 133-07-3	0.5%	not established

None of the materials in this product are on the IARC, NTP or OSHA carcinogen lists.
TWA = Time Weighted Average. The 50ppm Worker Exposure Limit is recommended by The Clorox Co. based on review of toxicological data.
TLV-TWA = Threshold Limit Value-Time Weighted Average.
Source: ACGIH.
PEL = Permissible Exposure Limit. Source: OSHA

IV Special Protection Information

Hygienic Practices: Wear safety glasses, gloves and protective clothing. If you experience headaches, nausea or dizziness leave the area until symptoms cease. Increase fresh air or wear a properly fitted respirator (NIOSH/MSHA TC-23) with an organic vapor cartridge. Wear a dust respirator while sanding.

Engineering Controls: Use general ventilation (fan, open windows, doors) to keep the mineral spirits exposure level below the Worker Exposure Limit.

Work Practices: Minimize skin and eye contact and inhalation of vapor and mist. Avoid inhalation of dust while sanding.

V Special Precautions

Keep out of reach of children. Avoid eye and skin contact and inhalation of vapor or mist. Avoid breathing dust while sanding. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful. **USE ONLY IN WELL VENTILATED AREA.** Do not use or store near open flame. Do not drink alcohol while working with this product. Do not drive, operate machinery or climb ladders if you experience headaches, nausea or dizziness.

VI Spill or Leak Procedures

Extinguish all sources of ignition in vicinity of spill. Ventilate with non-sparking fan to release vapors. Clean up spills as soon as possible. Absorb spills with clay or diatomaceous earth. Dispose of in accordance with local, state and federal regulations.

VII Reactivity Data

Stable under normal use and storage conditions.

VIII Fire and Explosion Data

Flash Point = 105°F/41°C (TCC)
 Flammable Limits: Lower = 1%, Upper = 6%
 Use foam, dry chemical, carbon dioxide or water spray as extinguishing material. To avoid spontaneous combustion of oily clothes and rags soak in water after use or place in a closed metal container away from building and other combustible material.

IX Physical Data

Boiling point -----315°F/157°C
 Flash point (TCC) -----105°F/41°C
 Solubility in water -----Insoluble
 Vapor Density (Air=1) -----4.9
 Vapor Pressure at 77°F -----2 mm Hg