

MATERIAL SAFETY DATA SHEET

MSDS Name: QUAD ADVANCED FORMULA SEALANT - Clear
MSDS Number: 24011-000-4
Version Number 4
Revision Date: SEP-27-2005
Page Number: 1

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: QUAD ADVANCED FORMULA SEALANT - Clear
HMIS Hazard Rating: Health: 1 Fire: 3 Reactivity: 0 PPE: B

Company Identification: HENKEL CONSUMER ADHESIVES
7405 PRODUCTION DRIVE
MENTOR OH 44060

Contact (24 hour): Customer Affairs (800)321-0253
Information phone/Fax: (440) 255-8900 / (440) 974-8358
CHEMTREC Emergency (24 hour): (703) 527-3887 (International)
(800) 424-9300
in Canada CANUTEC 613-996-6666

Product Class SEALANT
Trade Name PRO-SERIES
Product Code See above

SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredient Name	CAS Number	Percent	TSCA
XYLENE	1330-20-7	15 - 25	Y
STODDARD SOLVENT	8052-41-3	10 - 15	Y
ETHYL BENZENE	100-41-4	< 5.0	Y

Ingredient Notes:

Remaining ingredients are not considered OSHA hazardous.
Not recommended for interior use in occupied structures.
Use OSI's Pro-Series H2U Acrylic Urethane Sealant.

SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

Form: Clear, high viscosity caulk
Solubility (in water): insol.
pH Value, +/- .3: Not Applicable
Boiling Range: 280.°F - 380.°F (137.78°C - 193.33°C)
Vapor Pressure (mmHg): 23.@ 68.°F (20.°C)
Evaporation Rate: 0.9 times Slower than n-Butyl Acetate

Vapor Density: Heavier than air

MATERIAL SAFETY DATA SHEET

MSDS Name: QUAD ADVANCED FORMULA SEALANT - Clear
MSDS Number: 24011-000-4
Version Number 4
Revision Date: SEP-27-2005
Page Number: 2

% Volatile, Weight approx. 35.%
% Volatile, Volume approx. 40.%
Specific Gravity: 0.927
VOC (less H2O or exempt) 340 Gr/L (35%)

NOTE:

*BOIL RANGE, EVAP RATE, VAPOR DENSITY AND PRESSURE FOR SOLVENT ONLY!

SECTION IV - FIRE FIGHTING MEASURES (Flash,UEL,LEL for solvent only)

Flammability Class IC
Flash Range: 80.°F (26.67°C)
Tag Closed Cup
Explosive Range (LEL/UEL): 1.%
7.%

EXTINGUISHING MEDIA:

Carbon Dioxide---Dry Chemical---Foam
Use water fog to cool material in vicinity of fire.

SPECIAL FIRE-FIGHTING PROCEDURES:

Use self-contained breathing apparatus with full facepiece
operated in pressure demand with full protective equipment.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Any closed container may rupture when exposed to extreme heat.
Solvent vapors are heavier than air and travel along the ground.
Vapors given off are flammable and may be ignited in air explosively.

SECTION V - HEALTH HAZARD DATA

ROUTES OF ENTRY:

ENTRY THROUGH... Inhalation and skin most likely

CARCINOGENICITY...

NTP? N/E | IARC Monographs? N/E | OSHA? NO
This product contains Ethylbenzene. The International Agency for
Research on Cancer has evaluated ethylbenzene and classified it as
a possible human carcinogen (Group 2B) based on sufficient evidence
for carcinogenicity in experimental animals, but inadequate evidence
for cancer in exposed humans.

EFFECTS OF OVEREXPOSURE

Eyes: Can cause irritation, redness, tearing and blurred vision.
Skin: Prolonged or repeated contact can cause moderate
irritation, drying of the skin, and dermatitis.
Inhalation: Excessive inhalation of vapors can cause respiratory
irritation, headache, drowsiness and fatigue. High
concentrations of vapors are anesthetic and may cause

MATERIAL SAFETY DATA SHEET

MSDS Name: QUAD ADVANCED FORMULA SEALANT - Clear
MSDS Number: 24011-000-4
Version Number 4
Revision Date: SEP-27-2005
Page Number: 3

central nervous system effects such as dizziness.
Ingestion: Can cause gastrointestinal irritation, nausea,
vomiting and diarrhea.

FIRST AID MEASURES

Eyes: Flush eyes gently with water for at least 15 minutes
lifting eyelids occasionally; get prompt medical attention
Skin: Wash thoroughly with soap and water; apply a mild skin cream.
Remove contaminated clothing.
Inhalation: Move affected person to fresh air; if breathing is
difficult, administer oxygen; if breathing has stopped,
give artificial respiration. Get medical attention.
Ingestion: DO NOT INDUCE VOMITING! Get immediate medical attention.

CHRONIC HAZARDS

NOTICE: Reports have associated repeated and prolonged
occupational overexposure to solvents with permanent brain,
nervous system, liver or kidney damage or may cause cardiac
arrhythmia. INTENTIONAL misuse of this product by
deliberately inhaling its vapors may be harmful or fatal.
Overexposure to XYLENE may cause injury to Liver, Kidney and blood.

SECTION VI - STABILITY AND REACTIVITY

Stability: This product is stable
Hazardous Polymerization: Hazardous polymerization will not occur

INCOMPATIBILITY:

Keep away from strong oxidizing agents.

CONDITIONS TO AVOID:

Keep away from heat, spark, open flames and any ignition source.

HAZARDOUS DECOMPOSITION PRODUCTS:

Will produce fumes and smoke containing carbon monoxide and
dioxide under fire conditions.

SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES:

STEPS TO BE TAKEN IN CASE OF SPILL:

Eliminate all ignition sources. Ventilate confined areas.
(Open windows and doors). Wear appropriate protective clothing.
Cover with absorbent. Scoop into sealable safety container.

WASTE DISPOSAL METHOD:

Dispose of following local, state, and federal regulations.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
-----------	-------------	------------	-----------	----------

MATERIAL SAFETY DATA SHEET

MSDS Name: QUAD ADVANCED FORMULA SEALANT - Clear
MSDS Number: 24011-000-4
Version Number 4
Revision Date: SEP-27-2005
Page Number: 4

Table with 6 columns: Component Name, Concentration 1, Concentration 2, Concentration 3, Concentration 4, Concentration 5. Rows include XYLENE, STODDARD SOLVENT, and ETHYL BENZENE.

RESPIRATORY PROTECTION:

If TLV of the product is exceeded, a NIOSH/MSHA jointly approved air supply respirator is advised in the absence of proper ventilation. OSHA regulations also permit the use of other types of NIOSH/MSHA respirators under specified conditions. (See your safety equipment supplier for more information)

VENTILATION:

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV. Ventilate during application and curing of this product.

PROTECTIVE CLOTHING:

Rubber gloves should be worn where skin contact is likely. Wear impervious clothing and shoes.

EYE PROTECTION:

Chemical goggles or safety glasses should be worn.

HANDLING AND STORAGE PRECAUTIONS:

Keep away from heat, spark and flame. Keep out of reach of children. Keep container closed while not in use. Do not cut or burn recepticals that have contained a solvent based product. Do not reuse this container. Use only in a well ventilated area.

N/A=NOT APPLICABLE N/AV=NOT AVAILABLE N/E, N/est=NOT ESTABLISHED

SECTION IX - TRANSPORT INFORMATION: (not all sizes available)

GROUND TRANSPORT (DOT) - DOMESTIC

Units less than 5L (1.3 gallons liquid) i.e. cartridges

Proper Shipping Name: CONSUMER COMMODITY
Classification: ORM-D
DOT Label Required: ORM-D
Shipping Document: CONSUMER COMMODITY
ERG Code: 171

Units GREATER than 5L i.e. 5gal. pail, 50 gal.drum

MATERIAL SAFETY DATA SHEET

MSDS Name: QUAD ADVANCED FORMULA SEALANT - Clear
MSDS Number: 24011-000-4
Version Number 4
Revision Date: SEP-27-2005
Page Number: 5

Proper Shipping Name: ADHESIVE
Classification: CLASS 3
DOT Label Required: Flammable liquid, UN1133, Class 3
Shipping Document: ADHESIVE,3, UN1133, PG III
ERG Code: 128
AIR TRANSPORT (DOT) - DOMESTIC
Units less than 5L (1.3 gallons liquid) i.e. cartridges

Proper Shipping Name: CONSUMER COMMODITY
Classification: ORM-D
DOT Label Required: ORM-D-AIR
Shipping Document: Consumer Commodity, ORM-D
ERG Code: 171

Units GREATER than 5L i.e. 5gal. pail, 50 gal. drum
Proper Shipping Name: ADHESIVE
Classification: Class 3
DOT Label Required: Flammable Liquid, UN 1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PG III
ERG Code: 128

AIR TRANSPORT (IATA) - INTERNATIONAL
Units less than 5L (1.3 gallons liquid) i.e. cartridges

Proper Shipping Name: CONSUMER COMMODITY
Classification: class 9
Label Required: ID8000
Shipping Document: Consumer Commodity,9, ID8000
ERG Code: 9L

Units GREATER than 5L i.e. 5gal. pail, 50 gal. drum
Proper Shipping Name: ADHESIVE
Classification: Class 3
Label Required: Flammable Liquid, UN 1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PG III
ERG Code: 3L

MARINE - OCEAN TRANSPORT (IMDG)
Units less than 5L (1.3 gallons liquid) i.e. cartridges

Proper Shipping Name: ADHESIVE
Classification: Class 3
Label Required: Flammable Liquid, UN1133, Class 3, Ltd. Qty.
(on ocean container only, not req. on cartons)
Shipping Document: ADHESIVE,3, UN1133, PG III, LTD.QTY.
EMS Code: F-E, S-D

Units GREATER than 5L i.e. 5gal. pail, 50 gal. drum
Proper Shipping Name: ADHESIVE

MATERIAL SAFETY DATA SHEET

MSDS Name: QUAD ADVANCED FORMULA SEALANT - Clear
MSDS Number: 24011-000-4
Version Number 4
Revision Date: SEP-27-2005
Page Number: 6

Classification: Class 3
Label Required: Flammable Liquid, UN 1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PG III
EMS Code: F-E, S-D

SECTION X - REGULATORY INFORMATION:

SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Ingredient Name	CAS Number	Percent
XYLENE	1330-20-7	15 - 25
ETHYL BENZENE	100-41-4	< 5.0

SARA Section 311/312 Hazard Categories met:
Immediate (Acute) and Delayed (Chronic) Health Hazards
Chemical substances are TSCA listed.
California PROP.65 Chemicals: none known

DISCLAIMER:

The information contained herein is based on data available as of the date of preparation of this MSDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method, apparatus mentioned, and user must make his own investigation to determine the suitability of the information or products for his particular purpose, for the protection of the environment, and the health & safety of the users of this material.