

MATERIAL SAFETY DATA SHEET

MSDS Name: S.B.R.-100 Brand Window & Siding Caulk
MSDS Number: 10011-001
Version Number 3
Revision Date: NOV-29-2005
Page Number: 1

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: S.B.R.-100 Brand Window & Siding Caulk
HMIS Hazard Rating: Health: 1 Fire: 2 Reactivity: 0 PPE: B

Company Identification: HENKEL CONSUMER ADHESIVES
7405 PRODUCTION DRIVE
MENTOR OH 44060

Contact (24 hour): Customer Affairs (800)321-0253
Information phone/Fax: (440) 255-8900 / (440) 974-8358
CHEMTREC Emergency (24 hour): (703) 527-3887 (International)
(800) 424-9300
in Canada CANUTEC 613-996-6666

Product Class CAULK
Trade Name Pro-Series
Product Code 10011-xxx

SECTION II - INGREDIENT AND HAZARD INFORMATION

Table with 4 columns: Hazardous Ingredient Name, CAS Number, Percent, TSCA. Rows include MINERAL SPIRITS and Titanium Dioxide \*\*.

Ingredient Notes:
Remaining ingredients are not considered OSHA hazardous.
\*\*The main hazard for Titanium Dioxide is dust inhalation. Because of its incorporation into the caulk, exposure by inhalation is unlikely.
Not recommended for interior use in occupied structures.
Use OSI's Pro-Series H2U Acrylic Urethane Sealant.

SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

Form: Non-sag, paste-like caulk
Appearance/Color: Various colors
Odor: Mild mineral spirits
Solubility (in water): insoluble
pH Value, +/- .3: Not Applicable
Boiling Range: 300.°F - 310.°F (148.89°C - 154.44°C)
Vapor Pressure (mmHg): 10.@ 25.°C (77.°F)
Evaporation Rate: 0.08 times Slower than n-Butyl Acetate

MATERIAL SAFETY DATA SHEET

MSDS Name: S.B.R.-100 Brand Window & Siding Caulk
MSDS Number: 10011-001
Version Number 3
Revision Date: NOV-29-2005
Page Number: 2

Vapor Density: Heavier than air
% Volatile, Weight 29.%
% Volatile, Volume approx. 50.%
Specific Gravity: 1.34249
VOC (less H2O or exempt) 388 g/l (29%)

NOTE:

\*BOIL RANGE, EVAP RATE, VAPOR DENSITY AND PRESSURE FOR SOLVENT ONLY!

SECTION IV - FIRE FIGHTING MEASURES (Flash,UEL,LEL for solvent only)

Flammability Class II
Flash Point: 105.°F (40.56°C)
Tag Closed Cup
Explosive Range (LEL/UEL): 0.9%
6.%

EXTINGUISHING MEDIA:

Carbon Dioxide---Dry Chemical---Foam
Use water fog to cool material in vicinity of fire.

SPECIAL FIRE-FIGHTING PROCEDURES:

Use self-contained breathing apparatus with full facepiece
operated in pressure demand with full protective equipment.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Any closed container may rupture when exposed to extreme heat.
Solvent vapors are heavier than air and travel along the ground.
Vapors given off are flammable and may be ignited in air explosively.

SECTION V - HEALTH HAZARD DATA

ROUTES OF ENTRY:

ENTRY THROUGH... Inhalation and skin most likely

CARCINOGENICITY...

NTP? N/E | IARC Monographs? N/E | OSHA? NO

EFFECTS OF OVEREXPOSURE

Eyes: Can cause irritation, redness, tearing and blurred vision.
Skin: Prolonged or repeated contact can cause moderate
irritation, drying of the skin, and dermatitis.
Inhalation: Excessive inhalation of vapors can cause respiratory
irritation, headache, drowsiness and fatigue. High
concentrations of vapors are anesthetic and may cause
central nervous system effects such as dizziness.
Ingestion: Can cause gastrointestinal irritation, nausea,
vomiting and diarrhea.

FIRST AID MEASURES

**MATERIAL SAFETY DATA SHEET**

MSDS Name: S.B.R.-100 Brand Window & Siding Caulk  
MSDS Number: 10011-001  
Version Number 3  
Revision Date: NOV-29-2005  
Page Number: 3

-----  
Eyes: Flush eyes gently with water for at least 15 minutes  
lifting eyelids occasionally; get prompt medical attention  
Skin: Wash thoroughly with soap and water; apply a mild skin cream.  
Remove contaminated clothing.  
Inhalation: Move affected person to fresh air; if breathing is  
difficult, administer oxygen; if breathing has stopped,  
give artificial respiration. Get medical attention.  
Ingestion: DO NOT INDUCE VOMITING! Get immediate medical attention.

**CHRONIC HAZARDS**

NOTICE: Reports have associated repeated and prolonged  
occupational overexposure to solvents with permanent brain,  
nervous system, liver or kidney damage or may cause cardiac  
arrhythmia. INTENTIONAL misuse of this product by  
deliberately inhaling its vapors may be harmful or fatal.

-----  
**SECTION VI - STABILITY AND REACTIVITY**

Stability: This product is stable  
Hazardous Polymerization: Hazardous polymerization will not occur

**INCOMPATABILITY:**

Keep away from strong oxidizing agents.

**CONDITIONS TO AVOID:**

Keep away from heat, spark, open flames and any ignition source.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

Will produce fumes and smoke containing carbon monoxide and  
dioxide under fire conditions.

-----  
**SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES:**

**STEPS TO BE TAKEN IN CASE OF SPILL:**

Eliminate all ignition sources. Ventilate confined areas.  
(Open windows and doors). Wear appropriate protective clothing.  
Cover with absorbent. Scoop into sealable safety container.

**WASTE DISPOSAL METHOD:**

Dispose of following local, state, and federal regulations.

-----  
**SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Occupational Exposure Limits**

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
MINERAL SPIRITS	100.00 PPM	N/est	N/est	N/est	100.00 PPM

Titanium Dioxide \*\*

-----

**MATERIAL SAFETY DATA SHEET**

MSDS Name: S.B.R.-100 Brand Window & Siding Caulk  
MSDS Number: 10011-001  
Version Number 3  
Revision Date: NOV-29-2005  
Page Number: 4

-----  
10.00 mg/F3 N/est N/est N/est 15.00 mg/F3

**RESPIRATORY PROTECTION:**

If TLV of the product is exceeded, a NIOSH/MSHA jointly approved air supply respirator is advised in the absence of proper ventilation. OSHA regulations also permit the use of other types of NIOSH/MSHA respirators under specified conditions. (See your safety equipment supplier for more information)

**VENTILATION:**

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV. Ventilate during application and curing of this product.

**PROTECTIVE CLOTHING:**

Rubber gloves should be worn where skin contact is likely. Wear impervious clothing and shoes.

**EYE PROTECTION:**

Chemical goggles or safety glasses should be worn.

**HANDLING AND STORAGE PRECAUTIONS:**

Keep away from heat, spark and flame.  
Keep out of reach of children.  
Keep container closed while not in use.  
Do not cut or burn recepticals that have contained a solvent based product. Do not reuse this container.  
Use only in a well ventilated area.

-----  
N/A=NOT APPLICABLE N/AV=NOT AVAILABLE N/E, N/est=NOT ESTABLISHED

-----  
**SECTION IX - TRANSPORT INFORMATION: (not all sizes available)**

**GROUND TRANSPORT (DOT) - DOMESTIC**

Units less than 5L (1.3 gallons liquid) i.e. cartridges

Proper Shipping Name: CONSUMER COMMODITY  
Classification: ORM-D  
DOT Label Required: ORM-D  
Shipping Document: CONSUMER COMMODITY  
ERG Code: 171

Units GREATER than 5L i.e. 5gal. pail, 50 gal.drum

Proper Shipping Name: ADHESIVE  
Classification: CLASS 3  
DOT Label Required: Flammable liquid, UN1133, Class 3  
Shipping Document: ADHESIVE,3, UN1133, PG III  
ERG Code: 128

**AIR TRANSPORT (DOT) - DOMESTIC**

Units less than 5L (1.3 gallons liquid) i.e. cartridges

-----

**MATERIAL SAFETY DATA SHEET**

MSDS Name: S.B.R.-100 Brand Window & Siding Caulk  
MSDS Number: 10011-001  
Version Number 3  
Revision Date: NOV-29-2005  
Page Number: 5

-----

Proper Shipping Name: CONSUMER COMMODITY  
Classification: ORM-D  
DOT Label Required: ORM-D-AIR  
Shipping Document: Consumer Commodity, ORM-D  
ERG Code: 171

Units GREATER than 5L i.e. 5gal. pail, 50 gal. drum  
Proper Shipping Name: ADHESIVE  
Classification: Class 3  
DOT Label Required: Flammable Liquid, UN 1133, Class 3  
Shipping Document: ADHESIVE, 3, UN1133, PG III  
ERG Code: 128

**AIR TRANSPORT ( IATA ) - INTERNATIONAL**

Units less than 5L (1.3 gallons liquid) i.e. cartridges

Proper Shipping Name: CONSUMER COMMODITY  
Classification: class 9  
Label Required: ID8000  
Shipping Document: Consumer Commodity,9, ID8000  
ERG Code: 9L

Units GREATER than 5L i.e. 5gal. pail, 50 gal. drum  
Proper Shipping Name: ADHESIVE  
Classification: Class 3  
Label Required: Flammable Liquid, UN 1133, Class 3  
Shipping Document: ADHESIVE, 3, UN1133, PG III  
ERG Code: 3L

**MARINE - OCEAN TRANSPORT ( IMDG )**

Units less than 5L (1.3 gallons liquid) i.e. cartridges

Proper Shipping Name: ADHESIVE  
Classification: Class 3  
Label Required: Flammable Liquid, UN1133, Class 3, Ltd. Qty.  
(on ocean container only, not req. on cartons)  
Shipping Document: ADHESIVE,3, UN1133, PG III, LTD.QTY.  
EMS Code: F-E, S-D

Units GREATER than 5L i.e. 5gal. pail, 50 gal. drum  
Proper Shipping Name: ADHESIVE  
Classification: Class 3  
Label Required: Flammable Liquid, UN 1133, Class 3  
Shipping Document: ADHESIVE, 3, UN1133, PG III  
EMS Code: F-E, S-D

-----  
**SECTION X - REGULATORY INFORMATION:**  
-----

**MATERIAL SAFETY DATA SHEET**

MSDS Name: S.B.R.-100 Brand Window & Siding Caulk  
MSDS Number: 10011-001  
Version Number 3  
Revision Date: NOV-29-2005  
Page Number: 6

-----

SARA Section 311/312 Hazard Categories met:  
Immediate (Acute) and Delayed (Chronic) Health Hazards  
Chemical substances are TSCA listed.  
SARA Section 313 toxic chemicals: NONE above the de minimis  
reporting thresholds.  
California PROP.65 Chemicals: none known

**DISCLAIMER:**

The information contained herein is based on data available as of the date of preparation of this MSDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method, apparatus mentioned, and user must make his own investigation to determine the suitability of the information or products for his particular purpose, for the protection of the environment, and the health & safety of the users of this material.