

Material Safety Data Sheet

DATE OF PRINTING: 03/06/2003

HMIS: H2F2R1

Section 1

MANUFACTURER: PERFORMANCE COATINGS INC.
360 Lake Mendocino Drive
Ukiah, California 95482

TELEPHONE: (707) 462-3023

PRODUCT CLASS: Semitransparent Stain

CODE IDENTIFICATION: Penofin®

TRADE NAME: Penofin Exterior and Interior oil – (various colors) Low V.O.C. II formula

EMERGENCY TELEPHONE NUMBERS: FOR CHEMICAL EMERGENCY. Spill, leak, fire, exposure or accident. Call CHEMTREC - Day or Night - 1-800-424-9300. Outside the United States call 202-483-7616.

EMERGENCY POISONING TREATMENT INFORMATION: Call collect 24 hours a day – 1-800-947-2331

DOT SHIPPING NAME: Paint Related Material 3, UN1263 PGIII (pkg. Exception 173.150)

Section 2 - Hazardous Ingredients

	PERCENT BY WEIGHT	ACGIH TLV* PPM mg./m3	OSHA PEL* PPM mg./m3
142 Solvent CAS Number 064742-88-7	16.08%	100 PPM	100 PPM
Xylene CAS Number 1330-20-7	5.36%	100 PPM	100 PPM
Ethyl Benzene CAS Number 100-41-4	1.07%	100 PPM	100 PPM
		*Threshold Limit Value	*Permissible Exposure Limit

brain damage and nervous system damage.

Section 5 - Health Hazard Data (Cont'd)

EMERGENCY FIRST AID PROCEDURES:

INHALATION: Move to fresh air.

SKIN: Promptly remove contaminated clothing and wash with soap and water.

EYES: Irrigate immediately with water or saline for at least 10-15 minutes.

INGESTION: Do not induce vomiting. Call a physician immediately and/or transport to emergency facility immediately.

Section 6 - Reactivity Data

STABILITY: (Conditions to avoid) Avoid open flames, welding arcs or other high temperature sources which induce thermal decomposition. Avoid strong oxidants.

HAZARDOUS DECOMPOSITION PRODUCTS: Hydrogen chloride and very small amounts of phosgene and chlorine.

HAZARDOUS POLYMERIZATION: Will not occur.

Section 7 - Spill or Leak Procedure

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: **SMALL LEAKS:** Mop up, wipe up, or soak up immediately remove to out-of-doors.

LARGE SPILLS: Evacuate area. Contain liquid; transfer to closed metal containers. Keep out of water supplies.

DISPOSAL METHOD: When disposing of the unused contents, the preferred options are to send to licensed reclaimer, or to permitted incinerators. Any disposal practice must be in compliance with federal, state and local regulations. Do not dump into sewers, on the ground, or into any body of water.

Section 8 - Special Protection Information

RESPIRATORY PROTECTION: Use a supplied air respirator when airborne exposure limits are exceeded.

VENTILATION: Control airborne concentrations below the exposure guideline. Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations. Lethal concentrations may exist in areas with poor ventilation.

Section 8 - Special Protection Information (cont'd)

SKIN PROTECTION: For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or frequently repeated contact could occur, use protective clothing impervious to this material. Selection of specific items such as gloves, boots, apron, or fully body suit will depend on operation.

EYE PROTECTION: Use safety glasses. Where contact with liquid is likely, chemical goggles are recommended.

OTHER PROTECTIVE EQUIPMENT: It is suggested that a source of clean water be available in work area for flushing eyes and skin.

Section 9 - Special Precautions

PRECAUTIONS TO BE TAKEN IN HANDLING OR STORING: Do not store above 125 °F.

OTHER PRECAUTIONS: Do not take internally. Do not use in areas of inadequate ventilation.

Section 10 - Sara 313 Information

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR Part 372:

<u>CHEMICAL NAME</u>	<u>CAS NUMBER</u>	<u>% BY WEIGHT</u>
Xylene	1330-20-7	5.36%
Ethyl Benzene	100-41-4	1.07%

PREPARED BY: Regulatory Director, Performance Coatings Inc., Ukiah, California 95482

REFERENCE DATE: March 2003

WARNING

Detectable amounts of some chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm may be found in various petroleum products and chemical products you purchase from Performance Coatings Inc., in their vapors, or may result from their use. Use care when handling or using all chemical and petroleum products.

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA BELIEVED TO BE CORRECT. HOWEVER, NO GUARANTEE OR WARRANTY OF ANY KIND EXPRESSED OR IMPLIED IS MADE WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.