



MATERIAL SAFETY DATA SHEET
 UNIVERSAL FOREST PRODUCTS®, INC.
 2801 East Beltline NE, Grand Rapids, Michigan 49525
 (616) 364-6161
 www.ufpi.com



SECTION 1 – PRODUCT IDENTIFICATION

PRODUCT NAME:	ProWood[®] <i>MICRO</i>
SYNONYMS:	Copper Quat treated wood Wood pressure treated with "micronized" copper and quaternary ammonium wood preservatives ProWood Micro with Microshades (a colorant) ProWood Micro treated wood products with water repellent ProWood Micro treated wood products with mold inhibitor ProWood Micro treated formaldehyde bonded products (plywood).
DESCRIPTION:	Wood, often green colored. May be dyed to various shades.
PURPOSE:	For use where wood is subject to decay or termite attack.
PREPARED BY:	Legal Compliance Department

SECTION 2 – HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

CAS #	Hazardous Component	Percent ¹
N/A	Wood/Wood dust	90-98.5
12069-69-1	Copper Carbonate expressed as Copper Oxides	0.3-1.0
Proprietary	Didecyl dimethyl ammonium carbonate and Didecyl dimethyl ammonium bicarbonate	0.1-0.5
1309-37-1	Red Iron Oxide ²	<1.0
51274-00-1	Yellow Iron Oxide ²	<1.0
50-00-0	Formaldehyde ³	0-8

¹The above values may vary due to the variability of treatment and the natural variability of wood

²Red and yellow iron oxide are present only in those products with added colorants (ProWood Micro with Microshades)

³Formaldehyde present only in those products bonded with formaldehyde based glues

This Product is considered hazardous under the criteria in 29 CFR 1910.1200 (Hazard Communication Standard) and the Canadian Workplace Hazardous Materials Information System.

SECTION 3 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Solid wood, appearance may vary	Specific Gravity:	Not Available
Odor:	Ammoniacal/wood odor	Vapor Pressure:	Not Available
Boiling Point:	Not Applicable	Vapor Density:	Not Applicable
Melting Point:	Not Applicable	Density:	Not Applicable
Freezing Point:	Not Applicable	% Volatile by Volume:	Not Applicable
Weight per Gallon:	Not Applicable	Solubility (H2O):	Not Applicable
Evaporation Rate:	Not Applicable	Reactivity (H2O):	Not Applicable

SECTION 4 – FIRE AND EXPLOSION HAZARD

Flash Point	Method	Upper/Lower Flammable Limit	Auto-ignition	Rate of Burn	Classification
Not Applicable	Not Applicable	Not Available	Not Available	Not Available	Combustible

Unusual Fire and Explosion Hazards: Wood is combustible, and wood dusts may form explosive mixtures with air in the presence of an ignition source. Combustion products may yield irritating and toxic fumes and gasses including amines and other organic materials, copper compounds, oxides of carbon and nitrogen.

Fire Fighting Equipment and Extinguishing Media: Use water to wet down wood to reduce the likelihood of ignition. Fire fighters should use full protective clothing including self-contained breathing apparatus.

NFPA Codes:	Health	1	HMIS Codes:	Health	1
	Flammability	1		Flammability	1
	Reactivity	0		Reactivity	0
	Other	N/A		Protection	B

Reactivity Data: Product is stable under normal conditions. Keep away from excessive heat, sparks, and open flames. Keep away from incompatible materials including strong reducing and oxidizing agents. Hazardous polymerization is not likely to occur.

SECTION 5 – HEALTH HAZARDS AND FIRST AID

WARNING! Wood dust may form an explosive mixture with air. Use exhaust ventilation when cutting, sawing or grinding in an enclosed area. Wood dust may cause irritation to eyes, skin, and upper respiratory tract. When cutting, sanding, or grinding avoid inhalation and wear safety glasses. Handling may cause splinters, use puncture resistant gloves. Do not burn pressure-treated wood in open fires, stoves, fireplaces, or residential boilers. Observe good hygiene and safety practices when handling this product.

	Signs and symptoms of acute overexposure	First Aid Measures
Eyes:	Wood dust may cause irritation to the eyes. Symptoms can include irritation, redness, scratching of the cornea, and tearing	Immediately flush eyes with water for at least 15 minutes. Seek medical attention if symptoms persist
Skin:	Prolonged contact with treated wood and/or treated wood dust may cause irritation to the skin. Any wood dust may cause irritation to the skin. Mechanical rubbing may increase skin irritation. Some wood species and their dusts may contain natural toxins, which may cause dermatitis or allergic reactions in sensitized individuals.	For irritation from skin contact flush immediately with soap and water, continue at least 15 minutes. If irritation persists, get medical attention immediately. If wood splinters are injected under the skin, get medical attention.
Ingestion:	If ingestion does occur, slight gastrointestinal irritation may result. Certain species of wood and their dusts may contain natural toxins, which can have adverse effects on humans.	If the material is swallowed, get medical attention or advice. Do not induce vomiting.
Inhalation:	Wood dust is irritating to the nose throat and lungs. Symptoms may include nasal dryness, deposits or obstructions in the nasal passages, coughing, sneezing, dryness and soreness of the throat and sinuses, hoarseness, and wheezing. Prolonged or repeated inhalation of wood dusts may cause respiratory irritation, recurrent bronchitis, and prolonged colds. Some species may cause allergic respiratory reactions with asthma-like symptoms in sensitized individuals. Prolonged exposure to wood dust by inhalation has been reported to be associated with nasal and paranasal cancer.	If dusts are inhaled, remove person to fresh air. If symptoms persist, seek medical attention.

Note to Physician: Respiratory ailments and pre-existing skin conditions may be aggravated by exposure to wood dust

Medical Conditions Generally Aggravated by Exposure to Wood Dust: Pre-existing eye, respiratory system and skin conditions.

Chronic Overexposure: Wood dusts may be irritating to the eyes, skin and respiratory tract. Prolonged or repeated inhalation of wood dust may cause respiratory irritation, recurrent bronchitis, and prolonged colds. Depending on the species of wood, recurrent exposure may cause allergic skin and respiratory reactions in some individuals.

Carcinogenicity: ProWood Micro treated wood and its components other than wood dust are not listed as carcinogens by ACGIH, NIOSH, or IARC. Wood dust is classified as a carcinogen by ACGIH, NIOSH, and IARC. This classification is based on an increased incidence of nasal and paranasal cancer in people exposed to wood dusts. Carcinogenicity of wood dust: ACGIH – A1 Confirmed Human Carcinogen (related to wood dusts-hard wood; NIOSH – Occupational carcinogen (related to wood dust); IARC – Monograph 62, 1995 (related to wood dust)(Group 1 (carcinogenic to humans)). IARC has listed formaldehyde as a probable human carcinogen.

SECTION 6 – EXPOSURE CONTROL MEASURES/PERSONAL PROTECTION

Personal Protective Equipment

- Eyes/Face:** Wear safety glasses with side shields when handling, cutting, sanding, or grinding this material. Use a face shield for processes that may generate excessive dusts and splinters.
- Skin:** Wear puncture resistant work gloves, such as leather when handling. Wear chemical resistant rubber gloves when handling freshly treated lumber at the treating facility.
- Respiratory:** Respirators must be worn if the ambient concentration of airborne contaminants exceeds prescribed exposure limits. Dust masks may be worn to avoid inhalation of nuisance dust. Dust masks may not be adequate protection in environments above the occupational exposure limit.
- Ventilation:** Cutting, grinding or sanding should be done outdoors or in a well ventilated area.

Component Exposure Limits*

Component	OSHA		ACGIH	
	PEL	STEL	TLV	TLV STEL
**Wood/Wood dust	15 mg/m ³ total dust 5 mg/m ³ respirable fraction (as a nuisance dust)	N/A	1 mg/m ³ TWA	10 mg/m ³ TWA
Copper Carbonate expressed as Copper Oxides	0.1 mg/m ³ TWA (fume)	N/A	0.2 mg/m ³ TWA (fume)	N/A
Didecyl dimethyl ammonium carbonate and Didecyl dimethyl ammonium bicarbonate	N/A	N/A	N/A	N/A
Red and Yellow Iron Oxide	10 mg/m ³ (total dust)	N/A	10 mg/m ³ (total dust)	N/A
Formaldehyde	0.75 ppm	2 ppm	0.3 ppm	N/A

**A state run OSHA program may have more stringent limits for wood dust and/or PNOR.

SECTION 7 – SAFE HANDLING, STORAGE, DISPOSAL, AND ACCIDENTAL RELEASE MEASURES

Handling Procedures:

- Do not generate airborne dusts in the presence of an ignition source when sawing, cutting or grinding wood.
- Some preservative may migrate from the treated wood into soil/water or may dislodge from the wood upon contact with skin. Wash exposed areas thoroughly. Wash hands after handling and before eating.
- Avoid contact of wood dusts with skin and eyes. Avoid breathing wood dusts.
- Do not eat, drink, or smoke when handling this product or in areas where dusts of this product are present.
- Do not use in direct contact with aluminum. Use hot-dip galvanized, stainless steel or other fasteners, hardware and sheet products as recommended by the hardware manufacturer.

Storage Procedures

- Maintain good housekeeping procedures, such as sweeping regularly to avoid accumulation of dusts.
- Store away from excessive heat, sparks, and open flame.

Disposal Procedures

- Do not burn pressure treated lumber in open fires, stoves, fireplaces, or residential boilers.
- Do not use as mulch.
- Dispose of waste material according to local, State, and Federal Regulations.

Accidental Release Measures

- No containment procedures are needed as this product cannot spill or leak the preservative.

SECTION 8 – HUMAN AND ECOLOGICAL TOXICITY

Ecotoxicity: The product is not expected to leach harmful amounts of preservative into the environment; however, some preservative may migrate into soil and water. The wood preservatives in this product contain insecticides and fungicides, which when released into the environment at high enough concentrations, are expected to adversely affect or destroy contaminated plants. They may be harmful or fatal to wildlife.

Toxicological and ecotoxicity testing have not been performed on this product. Environmental fate information not available.

SECTION 9 – REGULATORY INFORMATION

SARA Sec. 302 & 304: N/A

SARA Section 311/312: Acute Health: Yes Chronic Health: Yes Fire: Yes Pressure: No Reactive: No

SARA 313: Form R required for 1.0% de minimis concentration. (related to copper). Typical product retentions will be less than 1.0% copper.

FIFRA: This material contains the following chemical present on either the Listing of Pesticide Chemicals (40 CFR 180) or Pesticides Classified for Restricted Use as listed by FIFRA: Copper carbonate

DOT: Not Regulated

Marine Pollutant: This material contains copper complex, required by USDOT to be identified as a marine pollutant

NOTICE: THE INFORMATION AND RECOMMENDATIONS SET FORTH ARE BELIEVED TO BE ACCURATE. HOWEVER, UNIVERSAL FOREST PRODUCTS®, INC., MAKES NO WARRANTY WITH RESPECT TO AND DISCLAIMS ALL LIABILITY FROM RELIANCE ON THE INFORMATION.