



# ALL WEATHER BLACKTOP PATCH

## DESCRIPTION

SAKRETE® All Weather Blacktop Patch is a mixture of blended asphalts, aggregates and additives.

## FEATURES AND BENEFITS

- For applications of 1 inch to 4 inches in thickness
- Can be used in wet environments
- Longer shelf life than conventional blacktop
- Can be used in cold weather
- Remains workable from freezing to over 100°F (38°C)
- Superior bonding to wet and dry surfaces

## APPLICATIONS

- For repairing potholes in blacktop drives, walks and parking lots.

## SAFETY

Read and understand the MSDS before using this product. **Keep out of reach of children.**

## PREPARATION

Chisel out loose blacktop. Square up area to be patched ensuring that the sides are vertical. Avoid a birdbath shaped hole. Clean area to be patched. Remove all loose particles, dirt, grass, etc. If sub-base is unsound, remove the unsound portion of the sub-base and replace with clean compacted gravel or stone.

## PLACEMENT & COMPACTION

Pour a 2-inch layer of loose SAKRETE® All Weather Blacktop Patch into the area to be patched. Level the loose material and then compact to a 1-inch layer. Compact with a tamper or a 4-inch x 4-inch post. PLACE AND COMPACT additional layers until desired thickness is achieved.

Riding over the patch with a car will not provide sufficient compaction. Compaction must be sufficient to cause the stone in the blacktop to lock together and minimize voids in each layer. If the black top is not completely compacted, the patch will remain soft and the material may not stay in place. Properly compacted

SAKRETE® All Weather Blacktop Patch will continue to harden over time.

## TIPS FOR USE

SAKRETE® All Weather Blacktop Patch may be opened to traffic immediately after being thoroughly compacted. Under certain conditions the surface may remain tacky for a short period of time. If this occurs, a light layer of sand may be helpful. Do not apply driveway sealer to the patched area for a period of 60-90 days of warm weather.

## STORAGE

If stored in an airtight container, unused material may be usable up to six months later. In general, if the material can be easily removed from the container and there are no lumps, it may be suitable for use.

## PRECAUTIONS

- NOT RECOMMENDED for use as a curb, speed bump, ramp or for driveway extensions.

## COVERAGE

Bag size	Yield
25 lb. (11.3 kg)	.17 cu. Ft (.005 cu. m)
60 lb. (27.2 kg)	.4 cu. Ft. (.01 cu. m)

To determine the number of bags needed:  
Multiply (length x width x depth) divided by yield

## PACKAGING

25 lb. (11.3 Kg) bucket – UPC: 7-64661-16125-7  
60 lb. (27.2 Kg) bag – UPC: 7-64661-16060-1  
Not all sizes available in all areas

**WARNING!** Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Exposure may result in irritation of the skin or eyes.

## LIMITED PRODUCT WARRANTY

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the date the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement of defective product or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.

The SAKRETE Companies  
866-SAKRETE  
866-725-7383

Sakrete® and the background design are registered trademarks of SAKRETE, Inc., Cincinnati, OH 45217 ©2002