

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/25/2006

Reviewed on 09/25/2006

1 Identification of substance

Trade name: SPRUCE SMOKE GRAY
Product code: 0000980007
Manufacturer/Supplier: SEYMOUR OF SYCAMORE
 917 Crosby Avenue
 Sycamore, IL 60178
 (815)-895-9101, www.seymourpaint.com



Information department: Health & Safety Department
Emergency information: CHEMTEL 1-800-255-3924, 813-248-0585 if located outside the U.S.

2 Composition/Data on components

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
67-64-1	Acetone	22.52%
74-98-6	propane	18.88%
108-88-3	Toluene	13.75%
64742-89-8	VM&P Naptha	12.26%
106-97-8	n-butane	11.09%
64742-47-8	Mineral Spirits	4.33%
13463-67-7	titanium dioxide	2.95%
67-63-0	isopropyl alcohol	2.49%

Additional information: For the wording of the listed risk phrases refer to section 3.

3 Hazards identification

Hazard description:   Irritant
Extremely flammable

Physical dangers: Danger! Extremely flammable liquid and vapor in a pressurized container. Vapors may cause flash fire. Keep away from heat, sparks, and flame.
 Extremely flammable.
 Irritating to eyes and respiratory system.
 Vapours may cause drowsiness and dizziness
 Keep out of the reach of children.

Effects of short-term overexposure: Vapors cause irritation to the eyes, nose, throat, skin, and central nervous system. Symptoms may include dizziness, throat irritation, headache, fatigue, swelling of eyes, and nausea.

Effects of chronic overexposure: May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

NFPA ratings (scale 0 - 4): Health = 1
 Fire = 4
 Reactivity = 3

HMS-ratings (scale 0 - 4): Health= 1
 Fire= 4
 Physical Hazard= 3

4 First aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Contact physician or poison control center.

5 Fire fighting measures

Extinguishing agents: CO2, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.

Protective equipment: No special measures required.

USA

(Contd. on page 2)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/25/2006

Reviewed on 09/25/2006

Trade name: SPRUCE SMOKE GRAY

(Contd. of page 1)

6 Accidental release measures:**Personal safety****precautions:**

Wear protective equipment. Keep unprotected persons away.

Environmental safety**precautions:**Inform appropriate authorities in case of seepage into water course or sewage system.
Do not allow product to reach sewage systems or ground water.**Measures for cleaning/****collecting:**

Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up spills with inert absorbent material. Refer to section 13 for disposal information.

7 Handling and storage**Fire/explosion protection:**Do not spray on a naked flame or any incandescent material.
Do not smoke. Protect from electrostatic charges.**Storage requirements:**Observe pressurized container storage regulations. Consult with your local authorities.
Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.**8 Exposure controls and personal protection:****Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**TLV O Short-term value: 1782 mg/m³, 750 ppm
Long-term value: 600 mg/m³, 250 ppm**74-98-6 propane**PEL O 1800 mg/m³, 1000 ppm
REL O Short-term value: N.E. mg/m³, N.E. ppm
Long-term value: 1800 mg/m³, 1000 ppm
TLV O (4508) mg/m³, (2500) ppm**108-88-3 Toluene**TLV O Short-term value: 500 mg/m³, 300 ppm
Long-term value: 375 mg/m³, 200 ppm**106-97-8 n-butane**REL O 1900 mg/m³, 800 ppm
TLV O 1900 mg/m³, 800 ppm**64742-47-8 Mineral Spirits**TLV O 200 mg/m³
As total hydrocarbon vapor; Skin; (P)**67-63-0 isopropyl alcohol**PEL O 980 mg/m³, 400 ppm
REL O Short-term value: 1225 mg/m³, 500 ppm
Long-term value: 980 mg/m³, 400 ppm
TLV O Short-term value: 984 mg/m³, 400 ppm
Long-term value: 492 mg/m³, 200 ppm**Protective hygienic****measures:**

Keep away from foodstuffs and animal feed. Wash hands after use.

Breathing equipment:

Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:A respirator is generally not necessary when using this product outdoors or in large open areas. In cases of inadequate ventilation, a respiratory protective device should be worn to prevent overexposure.
Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.**Eye protection:**

Tightly sealed goggles

9 Physical and chemical properties:**General Information:**

Form:	Aerosol
Color:	According to trade name description in section 1.
Odor:	Solvent
Boiling point/Boiling range:	-44°C (-47°F)
Flash point:	-19°C (-2°F)

(Contd. on page 3)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 09/25/2006

Reviewed on 09/25/2006

Trade name: SPRUCE SMOKE GRAY

(Contd. of page 2)

Ignition temperature:	365.0°C (689°F)
Auto igniting:	Product is not self-igniting.
Danger of explosion:	Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	0.9 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor Pressure:	40 PSI, 2750 hPa
Density:	Not determined.
Specific Gravity:	Between 0.77 and 0.90 (Water equals 1.00)
VOC content:	493.1 g/l / 4.11 lb/gl
VOC in weight percent (less acetone):	49.3 %
Solids content:	15.0 %

10: Stability and reactivity:**Conditions to be avoided:** Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.**Possibility of Hazardous****Reactions:** No dangerous reactions known.**11: Toxicological information:****Primary effect on the skin:** No irritant effect.**Primary effect on the eye:** Irritating effect.**Sensitization:** No sensitizing effects known.**Additional toxicological****information:** Harmful**12: Ecological information:****Other information:** This product does not contain any chloroflourocarbons (CFC's), chlorinated solvents, lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyl (PBB), or polybrominated diphenyl ether (PDBE). No specific ecological data is available for this product.**Aquatic toxicity:** Harmful to aquatic organisms.

Hazardous for water, do not empty into drains.

13: Disposal considerations:**DISPOSAL METHOD:** Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.**Recommendation:** Empty cans should be recycled.**14: Transport information:**

Hazard class:	2.1
Identification number:	N/A
Label	2.1
ADR/RID class:	2 5F Gases
UN-Number:	1950
IMDG Class:	2.1
Packaging group:	II
EMS Number:	F-D,S-U
Marine pollutant:	No
ICAO/IATA Class:	2.1
Propper shipping name:	Aerosols, Flammable Consumer Commodity ORM-D

15: Regulations:**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

(Contd. on page 4)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 09/25/2006

Reviewed on 09/25/2006

Trade name: SPRUCE SMOKE GRAY

(Contd. of page 3)

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances Control Act):

All ingredients are listed.

PROPOSITION 65 Chemicals known to cause cancer:

1333-86-4 Carbon black

100-41-4 ethyl benzene

PROPOSITION 65

Chemicals known to cause developmental toxicity:

108-88-3 Toluene

Canadian WHMIS:

Class A, B5---Flammable Aerosols

EPA:

A= Known human carcinogen B= Probable human carcinogen

C= Possible human carcinogen

D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).

A= Known human carcinogen

B= Probable human carcinogen

C= Possible human carcinogen

D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).

IARC:

Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.

Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

13463-67-7 titanium dioxide

2B

67-63-0 isopropyl alcohol

3

ACGIH TLVs:

A1-designates a confirmed human carcinogen.

A2-designates a suspected human carcinogen.

A3-designates an animal carcinogen.

A4-designates "not classifiable as a human carcinogen".

13463-67-7 titanium dioxide

A4

NIOSH:

13463-67-7 titanium dioxide

1333-86-4 Carbon black

16. Other information:

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact: Regulatory Affairs