

SECTION 1 - MANUFACTURER INFORMATION

MANUF/DIST : CHEM-POWER MFG DIV/ FOSTER & CO., INC
15 Wing Drive EMERGENCY PHONE.....: 973-267-4100
Cedar Knolls PREPARATION/REVISION DATE: 08/22/03
NJ 07927
PREPARER/CONTACT: Gary Adams, Chemist
LOCATION : Whs 1

TRADE NAME/SYNONYMS...: SPRAYMATIC (Aerosol)
CHEMICAL NAME/SYNONYMS: Open Gear Lube
CHEMICAL FAMILY.....: Tackified Lubricant
FORMULA.....: Mixture
PRODUCT CODE.....: 19-35

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS)

* HEALTH..... 2 *
* FLAMMABILITY.. 3 *
* REACTIVITY.... 0 *
* PROTECTION.... B *

SECTION 2 - HAZARDOUS INGREDIENTS

THIS PRODUCT CONTAINS HAZARDOUS INGREDIENTS : YES

CHEMICAL/COMMON NAME	CAS-NUMBER	%	PEL-OSHA	TLV-ACGIH
Petroleum asphalt	8052-42-4	30-60	N/I	N/I
*n-Hexane	110-54-3	15-30	50 ppm	50 Ppm
Paraffin Oil	64741-89-5	2-8	5mg/m3	as mist
Propane	74-98-6	2-8	2500 ppm	1000 ppm
Butane	106-97-8	2-8	800 ppm	800 ppm
Isohexane isomers	107-83-5	2-8	500 ppm	500 ppm

*This ingredient is reportable under EPA SARA Title 111-please check applicable states for additional regulations.

THIS PRODUCT CONTAINS CARCINOGENS (NTP, IARC, or OSHA):NO

CHEMICAL/COMMON NAME	CAS-NUMBER	%	NTP	IARC	OSHA
N/A	N/A	N/A	N/A	N/A	N/A

SECTION 3 - HEALTH HAZARD DATA

HEALTH EFFECTS (Acute And Chronic)-
HAZARDS: Excessive inhalation may cause CNS depression, dizziness and headaches. Severe inhalation may cause liver damage and complications of heart

ailments. SKIN: May cause redness and irritation. INGESTION: Irritation of the gastrointestinal tract may result. Repeated or prolonged overexposure to Hexane may cause damage to nerve tissue of the arms and legs (peripheral neuropathy), resulting in muscular weakness and loss of sensation. Repeated or prolonged overexposure to solvents may cause brain damage and nervous tissue damage.

PRIMARY ROUTES OF ENTRY-
Inhalation, skin, ingestion.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE-
May aggravate existing eye, skin, upper respiratory conditions.

EMERGENCY FIRST AID PROCEDURES-
EYE CONTACT: Flush with water for 15 minutes. If irritated, see physician.
SKIN CONTACT: Wash with soap and water. If irritated, see physician.
INHALATION: Remove to fresh air. Resuscitate if necessary. Get medical aid.
INGESTION: DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY.

SECTION 4 - CHEMICAL DATA

BOILING POINT (F).....: N/A	SPECIFIC GRAVITY (WATER=1).....: 0.76
VAPOR PRESSURE (mmHg): 60 psi	PERCENT VOLATILE BY VOLUME (%): N/I
VAPOR DENSITY (AIR=1): >1.0	EVAPORATION RATE (N-Butyl Acetate =1): >1

SOLUBILITY IN WATER-
Nil

APPEARANCE AND ODOR INFORMATION-
Brown/Solvent Odor.

SECTION 5 - PHYSICAL HAZARD DATA

FLASH POINT (Method Used): N/A FLAMMABLE LIMITS : Lel=1.0 UEL=9.5

EXTINGUISHING MEDIA-
Use water fog, dry chemical, carbon dioxide.

SPECIAL FIRE FIGHTING PROCEDURES-
Self contained breathing apparatus. Aerosol cans may rupture.

UNUSUAL FIRE AND EXPLOSION HAZARDS-
Flammable by CPSC Flame Extension Test.

INCOMPATIBILITY (Materials To Avoid)-
The above solvents are incompatible with strong oxidizers and active metals.

HAZARDOUS DECOMPOSITION PRODUCTS-
In fire will decompose to water, carbon dioxide, halogen acids and phosgene.

SECTION 8 - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE-

Do not puncture or incinerate containers. Do not store at temperatures above 130F. Keep boxes and cans dry to prevent rust penetration.

MAINTENANCE PRECAUTIONS-

N/I

OTHER PRECAUTIONS-

Avoid food contamination. KEEP OUT OF REACH OF CHILDREN. Avoid breathing vapors.

Vapors are heavier than air and can accumulate in low areas (ie garage pits) be sure to provide adequate ventilation.

ADDITIONAL COMMENTS-

SHIPPING NAME: Consumer Commodity ORM-D. Warning: Contents under pressure. NOT SUITABLE FOR AIR TRANSPORT.

For transportation emergency call INFOTRAC 1-800-535-5053, 24hr/ 7 days.