MATERIAL SAFETY DATA SHEET SUPERCLEAN TOUGH TASK

I. PRODUCT & COMPANY INFORMATION

PRODUCT/MATERIAL NAME: CHEMICAL NAME: CHEMICAL FORMULA: CHEMICAL FAMILY/CLASSIFICATION	:	SUPERCLEAN TOUGH TASK Mixture NA Alkaline aqueous liquid	
MOLECULAR WEIGHT: MATERIAL USE:		NA Multi purpese elegper/degregger	
		Multi-purpose cleaner/degreaser	
HMIS HAZARD RATING: (0: Minimal; '	•	: Moderate; 3: Serious; 4: Severe)	
HEALTH:	3		
FLAMMABILITY:	0		
REACTIVITY:	1		
WARNING STATEMENT, IF APPLICABLE:		Danger! Causes eye and skin burns. Avoid contact.	
NTS, IF APPLICABLE:			
COMPANY NAME (In the U.S.):	SuperClean Brands, Inc.		
. ,	51 East Maryland Avenue		
	St Paul, MN USA		
	Telephone		
	•		
	Fax:	621.489.8247	
	Website:	www.superclean.com	

DATE PREPARED: March 8, 2006 DATE REVISED: August 14, 2006/ REV. 1

IN THE EVENT OF AN EMERGENCY, PLEASE CALL:

800.304.5068

II. INGREDIENT INFORMATION

INGREDIENTS: CHEMICAL/COMMON NAME	EXPOSURE LIMITS: TVL	LD50	LC50	%
Water	ND	ND	ND	60-100
CASRN 7732-18-5				
2-Butoxyethanol	PEL/TWA:25ppm	Oral, rabbit: 300 mg/kg	Inhalation, 7 hr.	5-10
CASRN 111-76-2	skin (OSHA, ACGIH)	Dermal, rabbit: 220 mg/kg	mouse: 700 ppm	
		Intravenous, rabbit: 252 mg/kg		
		Intraperitoneal, rat: 220 mg/kg		
Sodium xylene sulfonate	ND	ND	ND	1-5
CASRN 1300-72-7				
Nonylphenol ethoxylate	ND	ND	ND	1-5
CASRN 127087-87-0				
Sodium hydroxide	PEL/TWA: 2mg/m3	Oral, mouse: 40mg/kg	ND	1-5
CASRN 1310-73-2	(OSHA, ACGIH), Ceiling			
Sodium metasilicate	ND	Oral, mouse: 770mg/kg	ND	1-5
pentahydrate				
CASRN 6834-92-0				
Other additives	ND	ND	ND	0.5-1.5
CASRN: NA				
Dye and fragrances	ND	ND	ND	0.1-1
CASRN: NA				

NA: Not Applicable; ND: No Data Available

III. FIRST AID MEASURES

SIGNS AND SYMPTOMS

- Eye Contact: Irritation, redness, tearing, pain, Conjunctival swelling, burns may develop. Immediately flush with plenty of clean water for at least 15 minutes. Consult a physician immediately.
- Skin Contact: Irritation, redness, extreme dryness and peeling, scarring may develop. Remove clothing and immediately flush with plenty of clean water for at least 15 minutes. Consult a physician immediately.
- Respiratory Nasal and respiratory irritation, pneumonitis, tissue damage could occur. If inhaled, remove from area of exposure. If breathing is difficult or irritation persists, call a physician. If ingested, do not induce vomitting. Give plenty of water or milk and call physician immediately. Do not give anything by mouth to an unconscious or convulsing person.

IV. HEALTH HAZARD DATA

Exposure	Limits:
----------	---------

See Section II, Product/Ingredient

Primary routes of entry:

- X Eye Contact X Skin Contact
- Skin Absorption X Inhalation (Acute) Inhalation (Chronic) Ingestion

Effects of Exposure

Acute:	Danger! Corrosive liquid.
Eyes:	Can cause severe irritation of burns. Avoid contact.
Skin:	Can cause severe irritation of burns. Avoid contact.
Respiratory System:	Can cause irritation or burns following inhalation of mists.
Ingestion:	Can cause severe irritation or burns to digestive tract. Do not swallow.
Chronic:	No chronic effects known.

Medical Conditions Generally Aggrevated by Exposure:

Pre-exisiting skin disorders.

Toxicology Data (Product):

Acute Data (Median Lethal Dose - species) Oral LD50: rat - 8.2 glkg Dermal LD50: rabbit - ND Inhalation LD50: rat - ND

Irritancy Data

Eye irritation: rabbit - ND Skin irritation: rabbit - ND Sensitization: guinea pig - ND

NA: Not Applicable; ND: No Data Available

SECTION V: EMPLOYEE PROTECTION		
Ventilation:	General ventilation and local exhaust recommended. Build up of mists/vapors in the working atmosphere must be prevented.	
Respiratory Respirators:	Respiratory Respirators should be used when engineering or other when other controls are not technically feasible. Protection required: use only a MSHA/NIOSH approved air supplied respirator or an air-purifying respirator.	
Eyes: Gloves: Clothing: Footwear: Other: Work Hygienic Practices:	Safety goggles or face shield. Impervious type gloves, such as rubber, neoprene, nitrile, polyethylene Protective clothing such as a coverall or apron may be used to minimize skin contact. No special requirement. Eye wash and safety shower recommended in industrial setting. Avoid skin and eye contact. Do not wear contaminated clothing. Launder before re-use or discard. Wash hands thoroughly after handling.	
Storage/Handling:	Maintain ambient temperatures. Avoid prolonged breathing of mists. Use with adequate ventilation. Corrosive to the eyes and skin. Severe internal irritation and damage can result when ingested. Avoid contact with eyes, skin, or clothing. Do not swallow. Keep container tightly closed when not in use.	

Keep out of reach of children.

SECTION VI: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:
Vapor Pressure:
Percent Volatiles:
Solubility in Water:
pH-Value:
Odor Treshold:
Appearance, Odor & Physical State:
Specific Gravity (Water=1):
Vapor Density:
Evaporation Rate (Water=1):
Freeze Point:
Viscosity @ 40 'c, cSt:
Coefficient of Water/Oil Distribution:

212° F, 100° C ND 85-95% Complete Neat - 13.0; 2% - 11.7 NA Clear, purple liquid; lemon odor 1.04 ND 1 -28° F, 2° C ND NA	
---	--

SECTION VII: FIRE AND EXPLOSION DATA

Flammability:	х	Yes No	Aqueous fluid
Flash Point (COC): Fire Point (COC): Autoignition Temperature: Flammability Limits in Air, % Vol.: Extinguishing Media:		••	NA; Lower - NA
Special Firefighting Procedures/Unusual and Explosion Hazards:		Cool fire exposed with water. Do not enter confined areas without full protective equipment, including a positive pressure NIOSH approved self- contained breathing apparatus.	
Explosion Data: Sensitivity fo Mechanical Impact: Sensitivity to Static Charge:		NA NA	

NA: Not Applicable; ND: No Data Available

SECTION VIII: REACTIVITY

Stability: Hazardous Polymerization: Conditions and Materials to Avoid (Incompatibilities): Stable at ambient temperatures Will not occur Strong acids. Strong oxidizers. Avoid contact with glass. Smoke, fumes, oxides of carbon

Hazardous Combustion or Decombustion Products:

SECTION IX: ENVIRONMENTAL PROTECTION

CHEMTREC EMERGENCY PHONE NUMBER 1-800-424-9300. 24 HOURS for U.S. transportation related spills, leaks, fire, exposure, or accident.

Spill or leak procedures:

Use best engineering practices when attempting cleanup of a large spill.

Larger spills:

Wear respirator and appropriate protective clothing. Stop source of leak, if possible. Dike, contain spill and recover free liquid. Prevent entry into waterways. Neutralize and/or soak up residue with an inert absorbent such as clay, sand or other suitable materials. Store and dispose of properly. Flush area with water. Where feasible and appropriate, remove contaminated soil.

Small spills:

Neutralize and/or soak up spill with an inert absorbent such as clay, sand or other suitable material. Store in a closed container and dispose of properly.

Regulatory spill reporting requirements may apply. Contact governmental agency or legal counsel for advice.

Waste Disposal Method:

If discarded as supplied, material meets RCRA characteristic definition of corrosivity, 0002. The toxicity characteristic has not been evaluated. Under RCRA, the applicable hazardous waste classification must be evaluated prior to disposal of the material. Use of the product, processing contamination may render the resulting material hazardous or alter waste classification.

All recovered material should be packaged, labeled, transported, and disposed of or reclaimed in accordance with lcoal, state and Federal regulations regarding air pollution, water pollution or health.

CAUTION: Improper disposal or reuse of the empty container may be hazardous and illegal. Cutting or welding of empty containers may cause explosion or toxic fumes from residues. Do not pressurize or expose to open flame or heat. Keep container closed and drum bungs in place. RE to applicable governmental standards.

SECTION X: REGULATORY INFORMATION

TRANSPORTATION

Special Shipping Information/DOT Proper Shipping Name: Corrosive liquid, n.o.s., 8, UN1760, PG II, (sodium hydroxide, sodium silicate). Follow all requirements regarding transportation of a regulated material.

CHEMICAL CONTROL REGULATIONS

TSCA Status: All components of this material appear on the Toxic Substance Control Act Chemical Substances Inventory.

CEPA Status: All components of this material appear on the Canadian Domestic substances list.

Canadian Workplace Hazardous Material Identification System WHMIS Classification: Material is a controlled product.

Class A	Compressed Gas
Class 8-1	Flammable Gas
Class B-2	Flammable Liquids
Class B-3	Combustible Liquids
Class B-4	Flammable Solids
Class 8-5	Flammable Aerosols
Class C	Oxidizing Material
Class 8-6	Reactive Flammable Materials
Class D, Div. 1	Materials Causing Immediate and Serious Toxic Effects
Class D-1A	Very Toxic Materials
Class 0-1B	Toxic Materials
Class D, Div. 2	Materials Causing Other Toxic Effects
Class D, 2A	Very Toxic Materials
Class D, 2B	Toxic Materials
Class E	Corrosive Material
Class 0-3	Biohazardous Infectious Material
Class F	Dangerously Reactive Material

EPCRA: Emergency Planning and Community Right to Know Act (SARA Title III):

Section 302/304 Extremely Hazardous Substance:

CERLA: Section 102(a) Hazardous Substance

Sodium hydroxide. Reportable quantity for product = 25,000 pounds (11,250 kg.)

Section 311 Hazard Category

X X

Х

Acute (Immediate) Chronic (Delayed) Fire Sudden Release of Pressure Reactive Not Applicable

Section 313 Toxic Release Inventory Chemical/Category

Glycol Ethers, 6.5% (wt.) max.

U.S. State Right to Know Laws

New Jersey Worker and Community Right to Know Act, N.J.A.C. 8:59-5 Labeling Information: See Section II. California Safe Drinking Water Enforcement Act (Proposition 65): This product contains one or more chemicals know to the State of California to cause cancer or reproductive harm.

NA

XI: OTHER INFORMATION

*** NOTICE***

The information presented herein is compiled from sources considered to be dependable, believed to be accurate to the best of SuperClean Brands, Inc. knowledge and offered in good faith for the purpose of hazard communication. Because product use is beyond our control no warranty is given expressed or implied. SuperClean Brands, Inc. cannot assume any liability for the use of information contained herein. To determine applicability or effect of any law or regulation with respect to the product use is beyond our control no warranty is given expressed or implied. SuperClean Brands, Inc. cannot assume any liability, user should consult a legal advisor or appropriate governmental agency.