

DOW CORNING CORPORATION

Material Safety Data Sheet

Page: 1 of 7

Version: 1.3

Revision Date: 2006/01/23

DOW CORNING(R) 732 MULTI -PURPOSE SEALANT CLEAR

1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

Dow Corning Corporation
South Saginaw Road
Midland, Michigan 48686

24 Hour Emergency Telephone: (989) 496-5900
Customer Service: (989) 496-6000
Product Disposal Information: (989) 496-6315
CHEMTREC: (800) 424-9300

MSDS No.: 01890573

Revision Date: 2006/01/23

Generic Description: Silicone elastomer
Physical Form: Paste
Color: Colorless
Odor: Acetic acid odor

NFPA Profile: Health 2 Flammability 1 Instability/Reactivity 0

Note: NFPA = National Fire Protection Association

2. OSHA HAZARDOUS COMPONENTS

| <u>CAS Number</u> | <u>Wt %</u> | <u>Component Name</u> |
|-------------------|-------------|------------------------|
| 17689-77-9 | 1.0 - 5.0 | Ethyltriacetoxysilane |
| 4253-34-3 | 1.0 - 5.0 | Methyltriacetoxysilane |

The above components are hazardous as defined in 29 CFR 1910.1200.

3. HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Acute Effects

Eye: Direct contact may cause moderate irritation.
Skin: May cause moderate irritation.
Inhalation: Irritates respiratory passages very slightly.
Oral: Low ingestion hazard in normal use.

Prolonged/Repeated Exposure Effects

Skin: No known applicable information.
Inhalation: No known applicable information.
Oral: No known applicable information.

DOW CORNING(R) 732 MULTI -PURPOSE SEALANT CLEARSigns and Symptoms of Overexposure

No known applicable information.

Medical Conditions Aggravated by Exposure

No known applicable information.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

4. FIRST AID MEASURES

| | |
|-------------|--|
| Eye: | Immediately flush with water for 15 minutes. Get medical attention. |
| Skin: | Remove from skin and wash thoroughly with soap and water or waterless cleanser. Get medical attention if irritation or other ill effects develop or persist. |
| Inhalation: | No first aid should be needed. |
| Oral: | No first aid should be needed. |
| Comments: | Treat according to person's condition and specifics of exposure. |

5. FIRE FIGHTING MEASURES

| | |
|-----------------------------|---|
| Flash Point: | Not applicable. |
| Autoignition Temperature: | Not determined. |
| Flammability Limits in Air: | Not determined. |
| Extinguishing Media: | On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO ₂), dry chemical or water spray. Water can be used to cool fire exposed containers. |
| Fire Fighting Measures: | Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool. |
| Unusual Fire Hazards: | None. |

Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide. Formaldehyde.

6. ACCIDENTAL RELEASE MEASURES

DOW CORNING(R) 732 MULTI -PURPOSE SEALANT CLEAR

Containment/Clean up: Observe all personal protection equipment recommendations described in Sections 5 and 8. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Note: See section 8 for Personal Protective Equipment for Spills. Call (989) 496-5900, if additional information is required.

7. HANDLING AND STORAGE

Use with adequate ventilation. Product evolves acetic acid (HOAc) when exposed to water or humid air. Provide ventilation during use to control HOAc within exposure guidelines or use respiratory protection. Avoid eye contact.

Keep container closed and store away from water or moisture.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Component Exposure Limits**

| <u>CAS Number</u> | <u>Component Name</u> | <u>Exposure Limits</u> |
|-------------------|------------------------|---------------------------|
| 17689-77-9 | Ethyltriacetoxysilane | See acetic acid comments. |
| 4253-34-3 | Methyltriacetoxysilane | See acetic acid comments. |

Acetic acid is formed upon contact with water or humid air. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA 10 ppm and ACGIH TLV: TWA 10 ppm, STEL 15 ppm.

Engineering Controls

Local Ventilation: None should be needed.
General Ventilation: Recommended.

Personal Protective Equipment for Routine Handling

Eyes: Use proper protection - safety glasses as a minimum.

Skin: Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Suitable Gloves: Silver Shield(R). 4H(R).

DOW CORNING(R) 732 MULTI -PURPOSE SEALANT CLEAR

Inhalation: No respiratory protection should be needed.

Suitable Respirator: None should be needed.

Personal Protective Equipment for Spills

Eyes: Use proper protection - safety glasses as a minimum.

Skin: Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Inhalation/Suitable Respirator: No respiratory protection should be needed.

Precautionary Measures: Avoid eye contact. Use reasonable care.

Comments: Product evolves acetic acid (HOAc) when exposed to water or humid air. Provide ventilation during use to control HOAc within exposure guidelines or use respiratory protection.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Paste
Color: Colorless
Odor: Acetic acid odor
Specific Gravity @ 25°C: 1.04
Viscosity: Not determined.
Freezing/Melting Point: Not determined.
Boiling Point: Not determined.
Vapor Pressure @ 25°C: Not determined.
Vapor Density: Not determined.
Solubility in Water: Not determined.
pH: Not determined.
Volatile Content: Not determined.

Note: The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND REACTIVITY

Chemical Stability: Stable.

Hazardous Polymerization: Hazardous polymerization will not occur.

Conditions to Avoid: None.

DOW CORNING(R) 732 MULTI -PURPOSE SEALANT CLEAR

Materials to Avoid: Oxidizing material can cause a reaction. Water, moisture, or humid air can cause hazardous vapors to form as described in Section 8.

11. TOXICOLOGICAL INFORMATION**Special Hazard Information on Components**

No known applicable information.

12. ECOLOGICAL INFORMATION**Environmental Fate and Distribution**

Complete information is not yet available.

Environmental Effects

Complete information is not yet available.

Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

Ecotoxicity Classification Criteria

| Hazard Parameters (LC50 or EC50) | High | Medium | Low |
|----------------------------------|-------|------------------|-------|
| Acute Aquatic Toxicity (mg/L) | <=1 | >1 and <=100 | >100 |
| Acute Terrestrial Toxicity | <=100 | >100 and <= 2000 | >2000 |

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

13. DISPOSAL CONSIDERATIONS**RCRA Hazard Class (40 CFR 261)**

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No

State or local laws may impose additional regulatory requirements regarding disposal.

Call (989) 496-6315, if additional information is required.

14. TRANSPORT INFORMATION**DOT Road Shipment Information (49 CFR 172.101)**

Not subject to DOT.

Ocean Shipment (IMDG)

DOW CORNING(R) 732 MULTI -PURPOSE SEALANT CLEAR

Not subject to IMDG code.

Air Shipment (IATA)

Not subject to IATA regulations.

Call Dow Corning Transportation, (989) 496-8577, if additional information is required.

15. REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

EPA SARA Title III Chemical Listings**Section 302 Extremely Hazardous Substances (40 CFR 355):**

None.

Section 304 CERCLA Hazardous Substances (40 CFR 302):

None.

Section 311/312 Hazard Class (40 CFR 370):

Acute: Yes
Chronic: No
Fire: No
Pressure: No
Reactive: No

Section 313 Toxic Chemicals (40 CFR 372):

None present or none present in regulated quantities.

Supplemental State Compliance Information**California**

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

None known.

Massachusetts

| <u>CAS Number</u> | <u>Wt %</u> | <u>Component Name</u> |
|-------------------|-------------|-----------------------|
|-------------------|-------------|-----------------------|

DOW CORNING(R) 732 MULTI -PURPOSE SEALANT CLEAR

7631-86-9 7.0 - 13.0 Silica, amorphous

New Jersey

| <u>CAS Number</u> | <u>Wt %</u> | <u>Component Name</u> |
|-------------------|-------------|---------------------------------------|
| 70131-67-8 | > 60.0 | Dimethyl siloxane, hydroxy-terminated |
| 7631-86-9 | 7.0 - 13.0 | Silica, amorphous |
| 17689-77-9 | 1.0 - 5.0 | Ethyltriacetoxysilane |
| 4253-34-3 | 1.0 - 5.0 | Methyltriacetoxysilane |

Pennsylvania

| <u>CAS Number</u> | <u>Wt %</u> | <u>Component Name</u> |
|-------------------|-------------|---------------------------------------|
| 70131-67-8 | > 60.0 | Dimethyl siloxane, hydroxy-terminated |
| 7631-86-9 | 7.0 - 13.0 | Silica, amorphous |

16. OTHER INFORMATION

Prepared by: Dow Corning Corporation

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

(R) indicates Registered Trademark