Franklin International MATERIAL SAFETY DATA SHEET

MSDS Name: Assembly High Tack Flo MSDS Number: 002213708

Revision Date:

022103

Page Number:

1 of 3

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:

Assembly High Tack Flo none

CAS Number:

HMIS Hazard Rating:

Health: 1 Fire: 1 Reactivity: 0

Company Identification:

Franklin International 2020 Bruck Street Columbus OH 43207

Contact:

Franklin Technical Services (800) 877-4583 (614) 445-1493 Franklin Security

Telephone/Fax: Emergency Phone (24 Hour):

(614) 445-1300 (800) 424-9300 (703) 527-3887

Chemtrec (24 Hour): Chemtrec International:

Product Class Product Use: Product Code:

ALIPHATIC RESIN EMULSION

wood glue

Division:

Industrial Adhesives & Sealants

SECTION 2 - COMPOSITION AND INFORMATION ON INGREDIENTS
Hazardous Ingredients CAS Number Percen Hazardous Ingredients CAS Number Percent Product contains no hazardous ingredients or they are below reportable levels.

OSHA PELs & ACGIH TLVs are listed in Section 8 where applicable.

SECTION 3 - HAZARD IDENTIFICATION

EMERGENCY CVERVIEW:

Yellow colored water-based adhesive. Slippery in the wet state.

ROUTES OF ENTRY:

Ingestion: Yes Yes

Inhalation: Skin: Yes

INHALATION:

Vapors and/or aerosols which may be formed at elevated temperature may be irritating to eyes and respiratory tract. No reported incidents of adverse health affects resulting from

inhalation of vapors at room temperature.

INGESTION:

No hazard expected in normal industrial use. Ingestion is not a likely route of exposure.

SKIN:

Prolonged or repeated skin contact can cause irritation.

EYE:

Substance may cause moderate eye irritation. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None identified. CARCINOGENICITY:

IARC: No

NTP: Νo

OSHA: No

REPRODUCTIVE TOXICITY:
This product has not been evaluated for reproductive toxicity.

SECTION 4 - FIRST AID MEASURES

INHALATION:

Remove patient to fresh air, if discomfort persists seek medical attention.

INGESTION:

Franklin International MATERIAL SAFETY DATA SHEET

MSDS Name: Assembly High Tack Flo MSDS Number: 002213708

Revision Date:

022103

Page Number:

2 of 3

Call poison control center immediately. Follow their specific instructions. Do not induce vomiting.

SKIN:

Wash with soap and water. Contact a physician if irritation develops

or persists.

Hold eyelids apart and flush with plenty of water for at least 15 minutes. Seek medical attention.

SECTION 5 - FIRE-FIGHTING MEASURES

Flammability Class (OSHA) IIIB

Flash Point:

Not Applicable

Explosive Range:

Not Applicable

EXTINGUISHING MEDIA:

Use alcohol foam, carbon dioxide, water spray, or ABC dry chemical when fighting fires involving this product.
HAZARDOUS COMBUSTION PRODUCTS:
Oxides of carbon.
FIRE FIGHTING PROCEDURES:

Wear a NIOSH approved self-contained breathing apparatus.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

CONTAINMENT TECHNIQUES: Use inert absorbent to dike the spill. Keep away from drains.

CLEAN-UP:

over spill and shovel product/absorbent mixture into an approved container. If product has dried scrape up and place in an approved container.

SECTION 7 - HANDLING AND STORAGE

Empty drums should be completely drained, properly bunged and promptly returned to a reconditoner, or properly disposed of.
Use only in well ventilated area.

STORAGE:

Keep from freezing.

Store at temperatures between 50 F and 90 F. PRECAUTIONARY STATEMENT:

Keep out of the reach of children.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION Occupational Exposure Limits
ACGIH TLV ACGIH TLV-C ACGIH STEL OSHA STEL

OSHA STEL OSHA PEL

ENGINEERING CONTROLS:

Use local exhaust as needed to maintain occupational exposure limits. OTHER:
Facilities storing or utilizing any chemical should be equipped with an eyewash facility and a safety shower.
RESPIRATORY PROTECTION:

Where exposure limits may be exceeded select a NIOSH approved respirator with appropriate Protection Factor and cartridge for the specific contaminents. Follow requirements for respiratory protection in OSHA 1910.134.

EYE PROTECTION: Chemical splash goggles (ANSI Z97.1 or approved equivalent). SKIN PROTECTION:

Where skin contact can occur, wear impervious gloves.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Color:

Liquid Yellow

Franklin International MATERIAL SAFETY DATA SHEET

MSDS Name: Assembly High Tack Flo MSDS Number: 002213708

Revision Date: 022103 Page Number:

3 of 3

Odor:

Mild

Solubility (in water):

Dispersible in water

pH Value: Boiling Range/Point: Evaporation Rate:

4.8 4.8 210.°F

Slower than n-Butvl Acetate

% Volatile: Specific Gravity: VOC:

54.1% 1.10

0.085 LB/GAL

SECTION 10 - STABILITY AND REACTIVITY
Stability: This product is stable
Hazardous Polymerization: Hazardous polymerization will not occur

CONDITIONS TO AVOID:

2

INCOMPATIBLITY:

Strong acids and bases.
HAZARDOUS DECOMPOSITION PRODUCTS:
Oxides of carbon may be released during combustion.

SECTION 11 - TOXICOLOGICAL INFORMATION

Acute and chronic health effects are not expected as long as good industrial hygeine and safety precautions are followed.

SECTION 12 - ECOLOGICAL INFORMATION

This formulation has not been tested for environmental effects.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Disposal of this product must comply with all applicable federal, state and local regulations.

CONTAINER DISPOSAL:

Disposal of this container should comply with all applicable federal, state and local regulations.

SECTION 14 - TRANSPORT INFORMATION

none N/A

UN Number
UN Pack Group
UN Class
ICAO/IATA Class
IMDG Class Nonhaz Nonhazardous Nonhazardous Shipping Name Nonhazardous

Packaging may not be approved for shipping by air. Please contact Franklin International for further information.

SECTION 15 - REGULATORY INFORMATION

TSCA (Toxic Substances Control Act Inventory): All components of this product are listed on the TSCA inventory except as exempted.

SECTION 16 - OTHER INFORMATION

DISCLAIMER:

While the information and recommendations set forth herein are believed to be accurate as of the data hereof, Franklin International makes no warranty, express or implied, with respect thereto and disclaims all liability from reliance thereon.