



C O R P O R A T I O N

P.O. Box 4040 Medford, Oregon 97501
Telephone: (503) 773-2522 Fax: 779-9921

=====
SECTION I - IDENTIFICATION
=====

PRODUCT: Medium density fiberboard, wood-based panel product, formaldehyde free

TRADE NAME: Medite II
DATE PREPARED: 12/1/92
=====

SECTION II - HAZARDOUS INGREDIENTS
=====

<u>Ingredient</u>	<u>CAS No.</u>	<u>OSHA</u> <u>PEL</u>	<u>ACGIH</u> <u>TLV</u>
Mixed Softwoods	N/A	5 mg/m ³ TWA 10 mg/m ³ STEL	5 mg/m ³
Methylenebis (phenylisocyanate)	101-68-8	.02 ppmC	.005 ppm
Paraffinic wax	8002-74-2	2 mg/m ³	2 mg/m ³
Mineral Wax	N/A	N/A	N/A

=====
SECTION III - PHYSICAL & CHEMICAL CHARACTERISTICS
=====

BOILING POINT: N/A SPECIFIC GRAVITY: 0.6 - 0.99
VAPOR PRESSURE: N/A VAPOR DENSITY: N/A
% VOLATILE BY VOLUME: N/A EVAPORATION RATE: N/A
SOLUBILITY IN WATER: <0.1% pH (PRODUCT): 4.5 - 6.5
APPEARANCE & ODOR: Honey-blonde solid panel; woody odor.
=====

SECTION IV - FIRE & EXPLOSION HAZARDS
=====

FLASH POINT: N/A AUTO-IGNITION TEMP: N/A
FLAMMABLE LIMITS: LEL (wood dust) 40 mg/m³
EXTINGUISHER MEDIA: Class A
SPECIAL FIRE FIGHTING PROCEDURES: None
UNUSUAL FIRE & EXPLOSION HAZARDS: None

=====
SECTION V - PHYSICAL HAZARDS (REACTIVITY DATA)
=====

STABILITY: Stable CONDITIONS TO AVOID: N/A
INCOMPATIBILITY: Strong acids, bases, oxidizing agents.
HAZARDOUS DECOMPOSITION PRODUCTS: Aldehydes, normal
products of wood combustion.

=====
SECTION VI - HEALTH HAZARDS
=====

WOOD DUST may produce allergic reactions in sensitive individuals; and may include contact dermatitis and irritation of the respiratory system.

Emergency First Aid Remove the affected individual to fresh air. Flush affected area with plenty of water (eyes) and wash with a mild soap if appropriate (skin). Seek medical treatment if symptoms persists, or if any allergic reaction is noted.

=====
SECTION VII - SPECIAL PRECAUTIONS & SPILL/LEAK PROCEDURES
=====

PRECAUTIONS Medite II should be stored under conditions which approximate end-use application; typically 65 - 80 degrees F, 30 -80% RH; and should not be co-stored with materials which offgas formaldehyde.

WASTE DISPOSAL Normally this material can be salvaged for use; otherwise incinerate or landfill in accordance with local, State and Federal regulations.

=====
SECTION VIII - SPECIAL PROTECTION INFORMATION
=====

VENTILATION High-efficiency wood dust removal and collection is necessary for woodworking operations.

RESPIRATORY PROTECTION meeting OSHA criteria if PEL is exceeded.

OTHER PROTECTIVE EQUIPMENT Safety goggles are recommended during remanufacturing operations.

=====



C O R P O R A T I O N

P.O. Box 4040 Medford, Oregon 97501
 Telephone: (541) 773-2522 Fax: (541) 770-9921

SECTION I - IDENTIFICATION

PRODUCT: Fire-resistant medium density fiberboard, wood-based panel product.
TRADE NAME: Medite FR.
DATE PREPARED: 7/28/95 rev.

SECTION II - HAZARDOUS INGREDIENTS

<u>Ingredient</u>	<u>CAS No.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Mixed Softwood	N/A	TWA-15 mg/m ³ (total) 5 mg/m ³ (respirable)	TWA-5 mg/m ³ STEL-10 mg/m ³ (15 min.)
Ammonium Polyphosphate	N/A	N/A	N/A
Methylenebis (Phenylisocyanate)	101-68-8	.02 ppmC	.005 ppm
Paraffinic Wax	8002-74-2	2 mg/m ³	2 mg/m ³
Mineral Wax	N/A	N/A	N/A

SECTION III - PHYSICAL & CHEMICAL CHARACTERISTICS

BOILING POINT: N/A	SPECIFIC GRAVITY: 0.6 - 0.99
VAPOR PRESSURE: N/A	VAPOR DENSITY: N/A
% VOLATILE BY VOLUME: N/A	EVAPORATION RATE: N/A
SOLUBILITY IN WATER: <0.1%	pH (PRODUCT): N/A
APPEARANCE & ODOR: Honey-blond solid panel; woody odor.	

SECTION IV - FIRE & EXPLOSION HAZARDS

FLASH POINT: N/A	AUTO-IGNITION TEMP: Varies (400 - 500 degrees F)
FLAMMABLE LIMITS: LEL (wood dust) 40 g/m ³	
EXTINGUISHER MEDIA: Class A	

Medite FR

Page 2

7/28/95

SPECIAL FIRE FIGHTING PROCEDURES: Use water to wet down wood dust to reduce the likelihood of ignition or dispersion of dust into the air. Remove burned or wet dust to open area after fire is extinguished.

UNUSUAL FIRE & EXPLOSION HAZARDS: Wood dust is a strong to severe explosion hazard if a dust "cloud" contacts an ignition source.

=====

SECTION V - PHYSICAL HAZARDS (REACTIVITY DATA)

STABILITY: Stable

CONDITIONS TO AVOID: N/A

INCOMPATIBILITY: Strong acids, bases, oxidizing agents and drying oils.

HAZARDOUS DECOMPOSITION PRODUCTS: Aldehydes, normal products of wood combustion.

=====

SECTION IV - HEALTH HAZARDS

WOOD DUST:

Skin & Eye Contact: Wood dust can cause eye irritation. Various species of wood dust can elicit allergic contact dermatitis in sensitized individuals.

Ingestion: Not applicable.

Skin Absorption: Not known to occur.

Inhalation: May cause nasal dryness, irritation and obstruction. Coughing, wheezing and sneezing; sinusitis and prolonged colds have also been reported.

Chronic Effects: Wood dust, depending on species, may cause dermatitis on prolonged, repetitive contact; may cause respiratory sensitization and/or irritation. IARC classifies wood dust as a carcinogen to humans (Group 1). This classification is based primarily on IARC's evaluation of increased risk in the occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with exposure to wood dust. IARC did not find sufficient evidence to associate cancers of the oropharynx, hypopharynx, lung, lymphatic and hematopoietic systems, stomach, colon or rectum with exposure to wood dust.

First Aid:

Eyes: Flush with water to remove dust particles. If irritation persists, get medical attention.

Skin: If a rash, persistent irritation or dermatitis occur, get medical advice where applicable before returning to work where wood dust is present.

Medite FR

Page 3

7/28/95

Inhalation: Remove to fresh air. If persistent irritation, severe coughing, or breathing difficulties occur, get medical advice before returning to work where wood dust is present.

Ingestion: Not applicable.

=====

SECTION VII - SPECIAL PRECAUTIONS & SPILL/LEAK PROCEDURES

PRECAUTIONS: Medite FR should be stored under conditions which approximate end-use application; typically 65 - 80 degrees F, 30 - 80% RH; and should not be co-stored with materials which offgas formaldehyde.

WASTE DISPOSAL: Normally this material can be salvaged for use; otherwise dispose in accordance with local, State and Federal regulations.

=====

SECTION VIII- SPECIAL PROTECTION INFORMATION

VENTILATION: High-efficiency wood dust removal and collection is necessary for woodworking operations.

RESPIRATORY PROTECTION: Meeting OSHA criteria if PEL is exceeded.

OTHER PROTECTIVE EQUIPMENT: Safety goggles are recommended during remanufacturing operations.

=====

SECTION IX - WARNING STATEMENTS

CALIFORNIA: "WARNING: This product may contain a chemical known to the State of California to cause cancer, or birth defects or other reproductive harm."

All phosphorus compounds may be reasonably expected to contain arsenic and possibly cadmium and/or lead in concentrations ranging from a few parts per billion to a few parts per million.

HAZARD WARNING: There is a possibility bicyclic phosphates or phosphites can be produced as a result of the thermal decomposition of this product in combination with trimethylol propane, trimethylol propane derived products or their corresponding trimethylol alkane homologs. Bicyclic phosphates and phosphites are a class of materials with acute neurotoxic properties which produce characteristic convulsive seizures in test animals. Therefore, this product should not be used in conjunction with trimethylol propane or trimethylol propane derived products.

