

Material Safety Data Sheet

DATE OF PRINTING: 01/24/05

HMIS: H1F0R0

Section 1

MANUFACTURER: PERFORMANCE COATINGS INC.
360 Lake Mendocino Drive
Ukiah, California 95482

TELEPHONE: (707) 462-3023

PRODUCT CLASS: Semi transparent Stain

CODE IDENTIFICATION: Penofin Concrete & Masonry Stain

TRADE NAME: Waterborne Latex – (various colors) 100 V.O.C. formula

EMERGENCY TELEPHONE NUMBERS: FOR CHEMICAL EMERGENCY. Spill, leak, fire, exposure, or accident. Call CHEMTREC - Day or Night - 1-800-424-9300. Outside the United States call 202-483-7616.

EMERGENCY POISONING TREATMENT INFORMATION: Call collect 24 hours a day – 1-800-947-2331.

DOT SHIPPING NAME: Paint Related Material 2, UN1263

Section 2 – Composition/Information on Ingredients

PERCENT BY WEIGHT

| | | |
|-------------|---------------------|-------|
| 142 Solvent | CAS NUMBER: MIXTURE | 2.70% |
|-------------|---------------------|-------|

| | | |
|---------------------------------|-------------------|-------|
| Dipropylene Glycol Methyl Ether | CAS NO:34590-94-8 | 3.22% |
|---------------------------------|-------------------|-------|

| | | |
|---------------|----------------------|-------|
| Triethylamine | CAS NUMBER: 121-44-8 | 0.61% |
|---------------|----------------------|-------|

| | | |
|----------------------------|--|--------|
| Non –hazardous ingredients | | 86.21% |
|----------------------------|--|--------|

Section 3 - Physical Data

PH: 8.5 TO 9.5
WEIGHT PER LB.S/GALLON 8.45
EVAPORATION RATE: Slower than ether. WEIGHT PER LB.S/ GALLON: 8.45
VAPOR DENSITY: GREATER THAN 1(AIR=1) . :
FLASH POINT: NO DATA
APPEARANCE AND ODOR: COLORED LIQUID SLIGHT

Section 4 - Hazard Data

Irritant

FLASH POINT: No Data
UNUSUAL FIRE OR EXPLOSION HAZARDS: Keep away from heat, sparks, or open flame.

SPECIAL FIRE FIGHTING PROCEDURES: Positive pressure self-contained breathing apparatus (SCBA) should be worn to avoid inhalation of concentrated vapors. Chemical protective clothing is recommended if there may be repeated or prolonged exposure to the liquid or concentrated vapors.

Section 5 – First Aid Measures

THRESHOLD LIMIT VALUE: See Section II

PRIMARY ROUTE(S) OF ENTRY: Dermal, ingestion, inhalation.

EFFECTS OF OVEREXPOSURE: Acute -Eye or skin contact may cause irritation. Can be irritating to the respiratory tract if inhaled as a mist or concentrated vapor. Inhalation of the vapors, or ingestion of the liquid, can cause systemic toxicity including dizziness, confusion, drowsiness, un-coordination, staggering gait, nausea, headache. Aspiration may also lead to chemical pneumonia
Chronic -Reports have associated repeated and prolonged overexposure to solvents with permanent brain damage and nervous system damage.

Section 5 – First Aid Measures (Cont'd)

EMERGENCY FIRST AID PROCEDURES:

INHALATION: Remove to fresh air.

SKIN: Promptly remove contaminated clothing and wash with soap and water, Get medical attention if irritation develops or persists.

EYES: Irritant, immediately with water or saline for at least 10-15 minutes.

INGESTION: Do not induce vomiting. Call a physician immediately and/or transport to emergency facility immediately.

Section 6 – Accidental Release Measures

PERSONAL PRECAUTIONS: see section 7

SPILLS: Absorb spill with inert material such as dry sand or sawdust, then place in a chemical waste container. Provide ventilation. Clean up spills immediately. Avoid any runoff into storm sewers, ditches and waterways.

Section 7- Special Protection Information

SKIN PROTECTION: For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or frequently repeated contact could occur, use protective clothing impervious to this material. Selection of specific items such as gloves, boots, apron, or fully body suit will depend on operation.

EYE PROTECTION: Use safety glasses. Where contact with liquid is likely, chemical goggles are recommended.

OTHER PROTECTIVE EQUIPMENT: It is suggested that a source of clean water be available in work area for flushing eyes and skin.

Section 8 - Special Precautions

PRECAUTIONS TO BE TAKEN IN HANDLING OR STORING: Do not store below 32 °_F. above 125°_F.

OTHER PRECAUTIONS: Do not take internally. Do not use in areas of inadequate ventilation.

Section 9 - Sara 313 Information

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR Part 372:

| <u>CHEMICAL NAME</u> | <u>CAS NUMBER</u> | <u>% BY WEIGHT</u> |
|---------------------------------|-------------------|--------------------|
| Dipropylene glycol methyl ether | 34590-94-8 | 3.22% |
| Triethylamine | 121-44-8 | 0.61% |
| Solvent 142 | Mixture | 2.70% |

PREPARED BY: Regulatory Director, Performance Coatings Inc., Ukiah, California 95482

REFERENCE DATE: January 24, 2005

WARNING

Detectable amounts of some chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm may be found in various petroleum products and chemical products you purchase from Performance Coatings Inc., in their vapors, or may result from their use. Use care when handling or using all chemical and petroleum products.

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA BELIEVED TO BE CORRECT. HOWEVER, NO GUARANTEE OR WARRANTY OF ANY KIND EXPRESSED OR IMPLIED IS MADE WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.