

99

MATERIAL SAFETY DATA SHEET



AUTOMOTIVE FINISHES

MANUFACTURER'S NAME
THE SHERWIN-WILLIAMS CO.
101 Prospect Avenue N.W.
Cleveland, Ohio 44115

EMERGENCY TELEPHONE NO.
(216) 566-2917
INFORMATION TELEPHONE NO.
(216) 566-2902
DATE OF PREPARATION
22-Apr-99

Section 1 — Product Identification

PRODUCT NUMBER AND NAME

988 Self Etching Primer

PRODUCT CLASS

Aerosol Specialty Product

Section 2 — Hazardous Ingredients

| CAS No. | INGREDIENT | % by WEIGHT | ACGIH-TLV | OSHA-PEL | Units | (mm Hg) |
|------------|---------------------------|-------------|--------------------------------------|-----------------|--------------------|---------|
| 74-98-6 | Propane | 11 | | 1000 | PPM | 760.0 |
| 106-97-8 | Butane | 11 | 800 | 800 | PPM | 760.0 |
| 108-88-33 | § Toluene. | 2 | 50 | 100 | PPM(Skin) | 22.0 |
| | | | STEL | 150 | | |
| 1330-20-7 | § Xylene. | 5 | 100 | 100 | PPM | 5.9 |
| | | | STEL | 150 | | |
| 67-64-1 | Acetone. | 31 | 750 | 1000 | PPM | 180.0 |
| | | | STEL | 1000 | | |
| 108-10-1 | § Methyl Isobutyl Ketone. | 18 | 50 | 50 | PPM | 16.0 |
| | | | STEL | 75 | | |
| 763-69-9 | Ethyl 3-Ethoxypropionate. | 2 | | Not Established | | 1.1 |
| 14807-96-6 | Talc | 7 | | 2 | Mg/M3 as Resp Dust | |
| 13463-67-7 | Titanium Dioxide. | 4 | 10 | 10[5] | Mg/M3 as Dust *** | |
| | | | *** Total Dust (Respirable Fraction) | | | |

§ Ingredient subject to the reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313, 40 CFR 372.65 C

Section 3 — Physical Data

| | | | |
|------------------|-------------|---------------------|-------------------|
| PRODUCT WEIGHT | 6.68 lb/gal | EVAPORATION RATE | Faster than Ether |
| SPECIFIC GRAVITY | 0.80 | VAPOR DENSITY | Heavier than Air |
| BOILING RANGE | <0-342 °F | MELTING POINT | N.Av. |
| VOLATILE VOLUME | 92 % | SOLUBILITY IN WATER | N.Av. |
| HMIS® RATING | 2 - 4 - 0 | PAINT-SAFE® CODE | J3 |

Section 4 — Fire And Explosion Hazard Data

FLAMMABILITY CLASSIFICATION FLASH POINT <0 °F PMCC LEL 1.0 UEL 12.8

RED LABEL — Extremely Flammable, Flash below 21 °F

EXTINGUISHING MEDIA -- Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section 5 — Health Hazard Data

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE Health Hazards

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

EMERGENCY AND FIRST AID PROCEDURES

If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
If on SKIN: Wash affected area thoroughly with soap and water.
Remove contaminated clothing and launder before re-use.
If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
If SWALLOWED: Get medical attention.

CHRONIC Health Hazards

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary, cardiovascular and reproductive systems.

Rats exposed to titanium dioxide dust at 250 mg./m3 developed lung cancer, however, such exposure levels are not attainable in the workplace.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Section 6 — Reactivity Data

STABILITY — Stable

CONDITIONS TO AVOID — None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS — By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION — Will Not Occur

Section 7 — Spill Or Leak Procedures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section 8 — Protection Information

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

Section 9 — Precautions

DOL STORAGE CATEGORY — 1A

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120 °F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Section 10 — Other Regulatory Information

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.