

MATERIAL SAFETY DATA SHEET

WAUWATOSA - BLDG 12  
 WIPING STAIN, MEADOW OAK  
 HALLMAN/LINDSAY

PRODUCT NAME: MEADOW OAK WIPING STAIN  
 PRODUCT CODE:

HMS CODES: H 7 R

2 2 1

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: HALLMAN/LINDSAY PAINTS  
 ADDRESS : P.O. BOX 109  
 SUN PRAIRIE, WI 53590

EMERGENCY PHONE : (608) 837-4538  
 INFORMATION PHONE : (608) 837-4538

DATE PRINTED : 11/11/96  
 NAME OF PREPARER : MICHAEL MC NULTY

===== SECTION II - HAZARDOUS INGREDIENTS/SAHA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
MINERAL SPIRITS 66 OSHA PEL: 500ppm, ACGIH TLV: 100ppm STEL TLV: N/A	64742-98-7	2 58	71.06
ODORLESS MINERAL SPIRITS OSHA PEL: 100ppm, ACGIH TLV: 100ppm	8052-41-3	2 58	5.51
HYDROUS CALCIUM MAGNESIUM SILICATE MIXTURE/TALC OSHA PEL: 2MG/M3, ACGIH TLV: 2MG/M3	14807-96-6		

\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*  
 Sanding the cured product may produce a nuisance dust. Observe a TLV of 10 mg/m3 for total dust containing no asbestos and <1% silica. Observe a TLV of 3mg/m3 for respirable dust.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 300 F - 340 deg F  
 VAPOR DENSITY: HEAVIER THAN AIR  
 COATING V.O.C.: 674 g/l  
 COATING V.O.C.: 5.63 lb/gal  
 SOLUBILITY IN WATER: INSOLUBLE  
 APPEARANCE AND ODOR: LIQUID WITH MILD ODOR

SPECIFIC GRAVITY (H2O=1): 0.86  
 EVAPORATION RATE: SLOWER THAN ETHER

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: 105 deg F  
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: .7  
 METHOD USED: T.C.C.  
 UPPER: 6

EXTINGUISHING MEDIA: DRY CHEMICAL, CARBON DIOXIDE, FOAM, ALCOHOL FOAM

SPECIAL FIREFIGHTING PROCEDURES

A water spray may cool containers. A stream of water may spread flames. Wear self contained breathing apparatus and goggles.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks & open flame. Combustible or explosive mixtures may form in air. Closed containers may explode when exposed to extreme heat. Never use welding torch on or near container [even empty] product and/or residue can explode.

===== SECTION V - REACTIVITY DATA =====

**STABILITY: STABLE**  
**CONDITIONS TO AVOID**

Avoid all possible sources of ignition. This material is flammable (or combustible per 49CFR 173.120 (b) (2) ) and may be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights etc.) Vapor is heavier than air and may collect in low areas.

**INCOMPATIBILITY (MATERIALS TO AVOID)**  
Strong oxidizing agents.**HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

Thermal decomposition may produce carbon monoxide, carbon dioxide, oxides of nitrogen and unidentifiable organic materials.

**HAZARDOUS POLYMERIZATION: Will Not Occur**

## ===== SECTION VI - HEALTH HAZARD DATA =====

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Adverse health effects from vapors or spray mists in poorly ventilated areas may include irritation of the mucus membranes of the nose, throat, and respiratory tract. Symptoms may also include headache, nausea, dizziness and confusion.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Prolonged or repeated contact with product may cause skin irritation, dermatitis, cracking. Eye contact- Severe irritation, tearing, redness, and blurred vision.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Can dry and defat skin causing cracks, irritation, and dermatitis.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE :**

Can cause gastrointestinal irritation, vomiting, nausea, and diarrhea. DO NOT TAKE INTERNALLY

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

Inhalation-Dizziness, headache, nausea, blurred vision, breathing difficulty. Eye contact-Severe irritation, tearing, redness, and blurred vision. Skin contact-Can dry and defat skin causing cracks, irritation, and dermatitis. Ingestion-Can cause gastrointestinal irritation, vomiting, nausea, and diarrhea. ACUTE OVEREXPOSURE MAY IRRITATE: respiratory tract (Nose, Throat, Lungs), Eyes, Skin. MAY PRODUCE THE FOLLOWING: Headache, Nausea, Central Nervous System Depression. CHRONIC OVEREXPOSURE MAY IRRITATE: Eyes, Skin. May Damage The Brain, Central Nervous System, Kidneys, Liver. MAY PRODUCE THE FOLLOWING: Headache, Nausea, Nervous System Depression Characterized By: Dizziness, Confusion, Unconsciousness, and Coma.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

Impaired Pulmonary Functions

**EMERGENCY AND FIRST AID PROCEDURES**

FIRST AID FOR INHALATION: Remove person to fresh air. Give oxygen if breathing is difficult.

FIRST AID FOR EYES: Flush eyes with water for at least 15 minutes. Call a Physician if irritation persists.

FIRST AID FOR SKIN: Wash with soap and water. Wash exposed clothing before reuse. See a Physician if irritation persists.

FIRST AID FOR INGESTION: If person is conscious, give two glasses of water and induce vomiting. See a Physician. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Eliminate ignition sources, provide good ventilation, dike spill to minimize contamination. Absorb with inert material. Collect in containers. Keep spill out of waterways.

**WASTE DISPOSAL METHOD**

Dispose of material in accordance with Federal, State and Local regulations.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Keep away from heat and open flames. Store in a cool and well vented area. Keep containers closed when not in use. Avoid prolonged contact with liquid and/or vapor. Do not store near heat, sparks, or flame. Store in a cool, dry, and well vented area. Keep containers closed when not in use. Ground all containers when transferring liquid. Use non sparking tools.

**OTHER PRECAUTIONS**

Smoking in areas where this material is used should be strictly prohibited. Never take internally. Wash thoroughly after use.

**===== SECTION VIII - CONTROL MEASURES =====****RESPIRATORY PROTECTION**

When spraying this material use a NIOSH approved cartridge respirator to keep airborne mists and vapor concentrations below TLV values.

**VENTILATION**

General mechanical ventilation or local exhaust should be suitable to keep the vapor concentrations below TLV values. Ventilation equipment must be explosion proof.

**PROTECTIVE GLOVES**

Impermeable chemical gloves for skin protection.

**EYE PROTECTION**

Chemical splash goggles.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

Use impermeable aprons and protective clothing whenever possible to protect skin from effects of overexposure. Eye wash. In poorly ventilated and confined spaces, use a fresh-air supplied respirator or self contained breathing apparatus.

**WORK/HYGIENIC PRACTICES**

Eye washes and safety showers in the workplace are recommended. Wash hands thoroughly with soap and water after applying product. When spraying this material, use a respirator (NIOSH/MSHA TC 23 C or equivalent)

**===== SECTION IX - DISCLAIMER =====**

This M.S.D.S. is furnished without charge to responsible persons who use it at their discretion and risk. Although the information and suggestions contained herein have been compiled, as of the issue date above, from sources believed to be reliable, there is no warranty of any kind, express or implied, as to the completeness and accuracy thereof.