

M A T E R I A L S A F E T Y D A T A S H E E T

WAUWATOSA / IDC - BLDG 12
STAIN - WIPING, SPRINGBROOK ON PINE
HALLMAN / LINDSAY

WIPING STAIN BASE

Spring Brook Pine

Page: 1

PRODUCT NAME: WIPING STAIN BASE
PRODUCT CODE:

Spring Brook Pine

HMS CODES: H P R
1 1 0

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: HALLMAN/LINDSAY PAINTS
ADDRESS: P.O. BOX 109
SUN PRAIRIE, WI 53590

DATE PRINTED: 7/11/2005
NAME OF PREPARER: MICHAEL MC NULTY
INFORMATION PHONE: (608) 834-6644
EMERGENCY PHONE: 1-800-688-4005

1/06

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE	WEIGHT
		MM HG @ TEMP	PERCENT
ODORLESS MINERAL SPIRITS OSHA PEL: 100ppm, ACGIH TLV: 100ppm	6150-41-1	0.48	81.33
HYDROUS CALCIUM MAGNESIUM SILICATE MIXTURE/TALC OSHA PEL: 2MG/M3, ACGIH TLV: 2MG/M3	14807-96-6		

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

Sanding the cured product may produce a nuisance dust. Observe a TLV of 10 mg/m³ for total dust containing no asbestos and 4% silica. Observe a TLV of 5mg/m³ for respirable dust.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 340 deg F
VAPOR DENSITY: HEAVIER THAN AIR
COATING V.O.C.: 694 g/l
COATING V.O.C.: 5.79 lb/gal
SOLUBILITY IN WATER: INSOLUBLE
APPEARANCE AND ODOR: LIQUID WITH MILD ODOR

SPECIFIC GRAVITY (H2O=1): .83
EVAPORATION RATE: SLOWER THAN ETHER
DENSITY: 6.9 lb/gal

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A
METHOD USED: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: .7 UPPER: 0
EXTINGUISHING MEDIA:
DRY CHEMICAL, CARBON DIOXIDE, FOAM, ALCOHOL FOAMS
SPECIAL FIREFIGHTING PROCEDURES
A water spray may cool containers. A stream of water may spread flames. Wear self contained breathing apparatus and goggles.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks & open flame. Combustible or explosive mixtures may form in air. Closed containers may explode when exposed to extreme heat. Never use welding torch on or near container (even empty) product and/or residue can explode.

SECTION V - REACTIVITY DATA

STABILITY: STABLE
CONDITIONS TO AVOID
Avoid all possible sources of ignition. This material is flammable (or combustible per 49CFR 173.120 (b) (2)) and may be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights etc.) Vapor is heavier than air and may collect in low areas.

INCOMPATIBILITY (MATERIALS TO AVOID)

Strong oxidizing agents.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS
Thermal decomposition may produce carbon monoxide, carbon dioxide, oxides of nitrogen and unidentifiable organic materials.

HAZARDOUS POLYMERIZATION: Will Not Occur

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

M A T E R I A L S A F E T Y D A T A S H E E T

WIPING STAIN BASE

Page: 2

Adverse health effects from vapors or spray mists in poorly ventilated areas may include irritation of the mucous membranes of the nose, throat, and respiratory tract. Symptoms may also include headache, nausea, dizziness and confusion.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Prolonged or repeated contact with product may cause skin irritation, dermatitis, cracking. Eye contact- Severe irritation, tearing, redness, and blurred vision.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can dry and de-fat skin causing cracks, irritation, and dermatitis. **INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**
Can cause gastrointestinal irritation, vomiting, nausea, and diarrhea. **DO NOT TAKE INTERNALLY** HEALTH HAZARDS (ACUTE AND CHRONIC OVEREXPOSURE MAY IRRITATE: respiratory tract (Nose, Throat, Lungs), Eyes, Skin. MAY PRODUCE THE FOLLOWING: Headache, Nausea, Central Nervous System Depression.

CHRONIC OVEREXPOSURE MAY IRRITATE: Eyes, Skin. May Damage The Brain, Central Nervous System, Kidneys, Liver. MAY PRODUCE THE FOLLOWING: Headache, Nausea, Nervous System Depression Characterized By: Dizziness, Confusion, Unconsciousness, and Coma.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No

CARCINOGEN CONTENT

N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Impaired Pulmonary Functions

EMERGENCY AND FIRST AID PROCEDURES

FIRST AID FOR INHALATION: Remove person to fresh air. Give oxygen if breathing is difficult.

FIRST AID FOR EYES: Flush eyes with water for at least 15 minutes. Call a Physician if irritation persists.

FIRST AID FOR SKIN: Wash with soap and water. Wash exposed clothing before reuse. See a Physician if irritation persists.

FIRST AID FOR INGESTION: If person is conscious, give two glasses of water and induce vomiting. See a Physician. **NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.**

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Eliminate ignition sources, provide good ventilation, dike spill to minimize contamination. Absorb with inert material Collect in containers. Keep spill out of waterways.

WASTE DISPOSAL METHOD

Dispose of material in accordance with Federal, State and Local regulations. **PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**
Avoid prolonged contact with liquid and/or vapor. Do not store near heat, sparks, or flame. Store in a cool, dry, and well vented area. Keep containers closed when not in use. Ground all containers when transferring liquid. Use non sparking tools.

OTHER PRECAUTIONS

Smoking in areas where this material is used should be strictly prohibited. Never take internally. Wash thoroughly after use. In keeping with good house-keeping practices, soiled rags and wiping cloths should be immersed in a container of water to reduce the potential of combustion.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION

When spraying this material use a NIOSH approved cartridge respirator to keep airborne mists and vapor concentrations below TLV values.

VENTILATION

General mechanical ventilation or local exhaust should be suitable to keep the vapor concentrations below TLV values. Ventilation equipment must be explosion proof.

PROTECTIVE GLOVES

Impervious chemical gloves for skin protection.

EYE PROTECTION

Chemical splash goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Use impervious aprons and protective clothing whenever possible to protect skin from effects of overexposure. Eye wash. In poorly ventilated and confined spaces, use a fresh-air supplied respirator or self contained breathing apparatus.

WORK/HYGIENIC PRACTICES

Eye washes and safety showers in the workplace are recommended. Wash hands thoroughly with soap and water after

M A T E R I A L S A F E T Y D A T A S H E E T

WIPING STAIN BASE

Page: 3

applying product. When spraying this material, use a respirator (NIOSH/MSHA TC 13 C or equivalent)

SECTION IX - DISCLAIMER

This M.S.D.S. is furnished without charge to responsible persons who use it at their discretion and risk. Although the information and suggestions contained herein have been compiled, as of the issue date above, from sources believed to be reliable, there is no warranty of any kind, express or implied, as to the completeness and accuracy thereof.